

## Libera Stand-alone


Design Artec  
Studio

iGuzzini

Last information update: April 2025

### Product configuration: RS47.Q2

RS47.Q2: Luminaire with Up/Down emission L=1428 - General Light - High Output - Space Frameless optic -- - 29.9W 3869.3lm - 3500K - CRI 90 - Sapphire blue/Black Transparent



### Product code

RS47.Q2: Luminaire with Up/Down emission L=1428 - General Light - High Output - Space Frameless optic -- - 29.9W 3869.3lm - 3500K - CRI 90 - Sapphire blue/Black Transparent

### Technical description

Direct (70%) / Indirect (30%) emission luminaire with 3500K CRI90 monochrome LED lamps. Opti-Diamond (High Output) Down General Light Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Up General Light optic with opal screen. Frameless version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000. Steel pendant mount cable with millimetric adjustment system and brass component. Ceiling-mounted base in painted aluminium with galvanised steel wall plate. Product supplied with DALI dimmable electronic power supply unit positioned inside the aluminium base.

### Installation

Pendant-mounted. Complete with power and pendant cables L=3000 with brass ceiling-fixing component

### Colour

Sapphire blue/Black Transparent (Q2)

### Weight (Kg)

1.55

### Mounting

ceiling pendant


### Wiring

Product complete with DALI power supply unit positioned inside the base.

Complies with EN60598-1 and pertinent regulations



IP20



### Technical data

|  |       |                                       |                                 |
|--|-------|---------------------------------------|---------------------------------|
| lm system:   | 3518  | Colour temperature [K]:               | 3500                            |
| W system:  | 29.9  | MacAdam Step:                         | 3                               |
| lm source:   | 4690  | Life Time LED 1:                      | > 50,000h - L90 - B10 (Ta 25°C) |
| W source:  | 27    | Lamp code:                            | LED                             |
| Luminous efficiency (lm/W, real value):            | 117.6 | Number of lamps for optical assembly: | 1                               |
| lm in emergency mode:                              | -     | ZVEI Code:                            | LED                             |
| Total light flux at or above an angle of 90° [Lm]: | 1293  | Number of optical assemblies:         | 1                               |
| Light Output Ratio (L.O.R.) [%]:                   | 75    | Control:                              | DALI-2                          |
| CRI (minimum):                                     | 90    |                                       |                                 |

### Polar

