

Last information update: April 2025

Product configuration: RT88.S4

RT88.S4: Luminaire L=880 - Neutral White - Integrated DALI - Very Wide Flood (Down) optic - 58.1W 8265lm - 4000K - CRI 90 - Black/Black/Black Transparent

**Product code**

RT88.S4: Luminaire L=880 - Neutral White - Integrated DALI - Very Wide Flood (Down) optic - 58.1W 8265lm - 4000K - CRI 90 - Black/Black/Black Transparent

Technical description

Luminaire made of painted extruded aluminium, frame and caps made of injection-moulded thermoplastic. Very Wide Flood optic (80°) in a Space Opti-Diamond (PMMA) version with a rear cover available in a White (Transparent White) or Black (Transparent Black) version. Integrated DALI dimmable power supply with CRI90 direct emission Neutral white (4000K) monochrome LED lamp (Mid-Power).

Installation

For an electrified track

Colour

Black/Black/Black Transparent (S4)


Weight (Kg)

2.73


Mounting

dali track|three circuit track

Complies with EN60598-1 and pertinent regulations

**Technical data**


Im system:	8541	Lamp code:	LED
W system:	63	Number of lamps for optical assembly:	1
Im source:	10950	ZVEI Code:	LED
W source:	63	Number of optical assemblies:	1
Luminous efficiency (Im/W, real value):	135.6	Power factor:	See installation instructions
Im in emergency mode:	-	Inrush current:	10 A / - µs
Total light flux at or above an angle of 90° [Lm]:	0	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 12 luminaires B16A: 20 luminaires C10A: 20 luminaires C16A: 34 luminaires
Light Output Ratio (L.O.R.) [%]:	78	Minimum dimming %:	1
CRI (minimum):	90	Overvoltage protection:	2kV Common mode & 1kV Differential mode
Colour temperature [K]:	4000	Control:	DALI-2
MacAdam Step:	3		

Polar

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	66	62	59	56	61	58	58	55	70
1.0	70	66	63	61	65	62	62	59	76
1.5	75	72	69	67	71	69	68	65	84
2.0	78	75	74	72	74	73	72	69	89
2.5	79	78	76	75	76	75	74	72	92
3.0	81	79	78	77	78	77	76	74	94
4.0	82	81	80	79	79	79	77	75	96
5.0	82	82	81	80	80	79	78	76	97

Luminance curve limit



UGR diagram

Corrected UGR values (at 10950 lm bare lamp luminous flux)											
Reflect.: ceil/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	16.6	17.3	16.9	17.5	17.8	15.7	16.4	16.0	16.7	16.9
	3H	16.5	17.1	16.8	17.4	17.7	15.6	16.2	15.9	16.5	16.8
	4H	16.4	17.0	16.8	17.3	17.6	15.5	16.1	15.9	16.4	16.7
	6H	16.4	16.9	16.7	17.2	17.6	15.4	16.0	15.8	16.3	16.6
	8H	16.3	16.9	16.7	17.2	17.5	15.4	15.9	15.8	16.3	16.6
	12H	16.3	16.8	16.7	17.2	17.5	15.4	15.9	15.8	16.2	16.6
4H	2H	16.4	17.0	16.7	17.3	17.6	15.5	16.1	15.9	16.4	16.7
	3H	16.3	16.8	16.6	17.1	17.5	15.4	15.9	15.8	16.3	16.6
	4H	16.2	16.6	16.6	17.0	17.4	15.3	15.8	15.7	16.2	16.5
	6H	16.2	16.5	16.6	16.9	17.4	15.3	15.6	15.7	16.0	16.5
	8H	16.1	16.5	16.6	16.9	17.3	15.2	15.6	15.7	16.0	16.4
	12H	16.1	16.4	16.6	16.8	17.3	15.2	15.5	15.6	15.9	16.4
8H	4H	16.1	16.4	16.5	16.9	17.3	15.3	15.6	15.7	16.0	16.5
	6H	16.0	16.3	16.5	16.8	17.2	15.2	15.5	15.7	15.9	16.4
	8H	16.0	16.3	16.5	16.7	17.2	15.1	15.4	15.6	15.9	16.4
	12H	16.0	16.2	16.5	16.7	17.2	15.1	15.3	15.6	15.8	16.3
12H	4H	16.0	16.4	16.5	16.8	17.2	15.2	15.5	15.7	16.0	16.4
	6H	16.0	16.2	16.5	16.7	17.2	15.1	15.4	15.6	15.9	16.4
	8H	16.0	16.2	16.5	16.7	17.2	15.1	15.3	15.6	15.8	16.3
Variations with the observer position at spacing:											
S =	1.0H	3.6 / -8.7					3.8 / -9.6				
	1.5H	6.3 / -9.7					6.2 / -10.3				
	2.0H	8.3 / -10.3					8.2 / -10.6				