


Last information update: June 2025

Product configuration: RU15.01+RV38.01+RU58.38

RU15.01: Minimal Down linear module - Surface or Pendant-mounted - for Opal or MPO screen - L=597 - White

RV38.01: Plate with Neutral White LED - Downlight UGR<19 - DALI - L=598 - 4.7W 428.8lm - 4000K - CRI 90 - White

RU58.38: Single Microprismatic screen L=1200 (UGR) - Opaline


Product code

RU15.01: Minimal Down linear module - Surface or Pendant-mounted - for Opal or MPO screen - L=597 - White

Technical description

Minimal (Frameless) version with extruded aluminium profile for surface or pendant-mounted application. Designed for use with an Opal or Microprismatic (MPO) single or roll screen (for continuous line versions). Version with direct light (Down) option.

Installation

Can be surface or pendant-mounted using accessories to be ordered separately.

Colour

White (01)

Wiring

Designed to house the LED modules and screens that can be used by the system.

Complies with EN60598-1 and pertinent regulations


Product code

RV38.01: Plate with Neutral White LED - Downlight UGR<19 - DALI - L=598 - 4.7W 428.8lm - 4000K - CRI 90 - White

Technical description

Neutral White LED plate with direct (Down) light emission. Version with UGR<19 controlled luminance ($L \leq 3000 \text{cd/m}^2$) ideal for environments with video monitors. To be combined with a Microprismatic screen (single or roll) to be ordered separately. The module optic and structural fittings allow high system efficiency values to be achieved. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables.

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

White (01)

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

Complies with EN60598-1 and pertinent regulations


Accessory code

RU58.38: Single Microprismatic screen L=1200 (UGR) - Opaline

Technical description

Flexible single Microprismatic screen for composition L=1200 - UGR< 19 optic -

Installation

snapped on via special springs located in the profile

Colour

Opaline (38)

Notes

TPa rated

Complies with EN60598-1 and pertinent regulations

Technical data

Im system:	429	Rg (Gamut Index):	95
W system:	4.7	Colour temperature [K]:	4000
Im source:	670	MacAdam Step:	3
W source:	3.5	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	91.2	Lamp code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of lamps for optical assembly:	1
Light Output Ratio (L.O.R.) [%]:	64	ZVEI Code:	LED
CRI (minimum):	90	Number of optical assemblies:	1
Rf (Colour Fidelity Index):	88	Control:	DALI-2

Polar