

Last information update: June 2025

Product configuration: RU27.01+RW16.83

RU27.01: Linear module - recessed Frame Down - for MMO/Space/Wall Washer versions - L=2384 - White

RW16.83: Plate with LED - Space optic - Downlight - General Light - HO - DALI - L=2384 - 55.1W 7062.5lm - 3500K - Black Transparent



Product code

RU27.01: Linear module - recessed Frame Down - for MMO/Space/Wall Washer versions - L=2384 - White

Technical description

Frame version extruded aluminium initial profile with contact frame, designed to house a specific LED plate in an MMO, Space and Wall Washer version.

Installation

Recessed using the brackets on the profile.



Colour

White (01)

Wiring

Designed to house the LED modules that can be used by the system.

Complies with EN60598-1 and pertinent regulations



Product code

RW16.83: Plate with LED - Space optic - Downlight - General Light - HO - DALI - L=2384 - 55.1W 7062.5lm - 3500K - Black Transparent

Technical description

3500K LED plate with a direct (Down) light emission in a version with a Space optic available in a Transparent White and a Transparent Black version. Translucent textured thermoplastic raster, created with a catadioptric system (patented Opti Diamond optic) - with no galvanic treatments - combined with a PP cover with a gloss finish and an additional diffuser screen. The resulting optic system generates an extremely elegant and professional light emission. General Light High Output (HO) version luminaire. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. Moulded and metallised polycarbonate raster.

Installation

Module insertion on profiles facilitated by a quick coupling system.

Colour

Black Transparent (83)

Wiring

Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable DALI power supply.

Notes

TPa version available on request, contact iGuzzini for more info.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	7063	Colour temperature [K]:	3500
W system:	55.1	MacAdam Step:	3
lm source:	9950	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	49	Lamp code:	LED
Luminous efficiency (lm/W, real value):	128.2	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	71	Number of optical assemblies:	1
CRI (minimum):	80	Control:	DALI-2

Polar

