

RZ00.L2: Pendant-mounted Stand Alone LED - Up/Down - DALI - GL - LO - Opal - L=1200 - 27W 3427.2lm - 3500K - White / Opal White


Product Code: 3427.2  
 RZ00.L2: Pendant-mounted Stand Alone LED - Up/Down - DALI - GL - LO - Opal - L=1200 - 27W 3427.2lm - 3500K - White / Opal White

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. 3500K LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) version for General Light profiles. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Opal PMMA diffuser screen. Pendant and power supply cables L=1500

## Pendant-mounted

White / Opal White (L2)

Complies with EN60598-1 and pertinent regulations



lm system:	3427	Colour temperature [K]:	3500
W system:	27	MacAdam Step:	3
lm source:	5040	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	24	Lamp code:	LED
Luminous efficiency (lm/W, real value):	126.9	Number of lamps for optical assembly:	1
lm in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	1479	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	68	Control:	DALI-2
CRI (minimum):	80		

<p><b>I<sub>max</sub></b>=799 cd</p> <p><b>C5-185</b></p>	<p><b>CIE</b></p> <p>nL 0.68</p> <p>51-82-97-57-68</p> <p>UGR 19.7-19.9</p> <p><b>DIN</b></p> <p>C.43</p> <p><b>UTE</b></p> <p>0.39D+0.29T</p> <p>F"1=512</p> <p>F"1+F"2=817</p> <p>F"1+F"2+F"3=967</p>
---	---