

iGuzzini

RZ62.U6: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - UGR<19 - LO - SPACE - L=1200 - 19W 2456.2lm - 3000K - CRI 90 - Aluminium/Black Transparent

RZ62.U6: Pendant-mounted Stand Alone - Warm White LED - Up/Down - DALI - UGR<19 - LO - SPACE - L=1200 - 19W 2456.2lm - 3000K - CRI 90 - Aluminium/Black Transparent

Stand Alone pendant-mounted luminaire. The product consists of an extruded aluminium profile with zamak end caps. Warm White LED plate with direct (Down) and indirect (Up) light emission. Low Output (LO) version with controlled luminance emission ($\leq 3000\text{cd/m}^2$) ideal for environments with video monitors ($\text{UGR} < 19$). Opti-Diamond Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. The module optic and structural fittings allow high luminous flux and system efficiency values. DALI dimmable power supply integrated in the luminaire. Extruded aluminium heat sink and "Halogen Free" electric cables. For indirect light (Up), we supply an extruded aluminium support plate that is painted white to increase reflection. Transparent PMMA raster with rear cover available in black or white PP according to the version. Pendant and power supply cables L=1500

Pendant-mounted

Aluminium/Black Transparent (U6)

4.48



Complies with EN60598-1 and pertinent regulations

Imax=2037 cd **C0-180**

CIE
nL 0.72
84-97-99-65-72
UGR 12.9-12.6

DIN
B.63

UTE
0.47 A+0.25 T
F"1=843
F"1+F"2=968
F"1+F"2+F"3=990

CIBSE
LG3 L<3000 cd/m² at 65°
UGR<16 | L<3000 cd/mq @