


Last information update: June 2025

Product configuration: SS79

SS79: 47 surface Integral with side box - Wall/Ceiling-mounted - Tunable white (2700K - 3500K - 5000K) - DALI - L = 340mm - Wall Grazing Wide Flood optic

**Product code**

SS79: 47 surface Integral with side box - Wall/Ceiling-mounted - Tunable white (2700K - 3500K - 5000K) - DALI - L = 340mm - Wall Grazing Wide Flood optic

Technical description

Direct light luminaire, designed to use Tunable White LED lamps (White 2700K, 3500K, 5000K), 220÷240Vac DALI dimmable with searching and addressing function. Ceiling, wall or surface-mounted. It consists of a body and installation brackets to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in Tunable White. The product is supplied with a nickel-plated brass PG13.5 single cable gland with H05RN-F 5x1, 5mm² rubber outlet cable with male IP68 connector. Fitted with a PMMA diffusing filter and optics with a plastic (methacrylate) lens for Wide Flood lighting. All external screws used are made of A2 stainless steel.

Installation

Installation accessories can be purchased separately, including arms (for heights < 3m and heights > 3m) and plates.

Colour

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

Mounting

wall arm|wall surface

Complies with EN60598-1 and pertinent regulations

**Technical data**

| | | | |
|--|-----------|---------------------------------------|-------------------------------|
| Im system: | 1277.5 | Colour temperature [K]: | Tunable white |
| W system: | 17.7 | Life Time LED 1: | 100,000h - L80 - B10 (Ta 25C) |
| Im source: | 1750 | Life Time LED 2: | 100,000h - L80 - B10 (Ta 40C) |
| W source: | 13 | Voltage [Vin]: | 230 |
| Luminous efficiency (Im/W, real value): | 72.18 | Lamp code: | LED |
| Im in emergency mode: | - | Number of lamps for optical assembly: | 1 |
| Total light flux at or above an angle of 90° [Lm]: | 0.0 | ZVEI Code: | LED |
| Light Output Ratio (L.O.R.) [%]: | 73 | Number of optical assemblies: | 1 |
| Beam angle [°]: | 16° / 66° | Intervallo temperatura ambiente: | from -30°C to 50°C. |
| CRI: | 80 | Control: | DALI-2 |