

Last information update: April 2025

Product configuration: ST03.01

ST03.01: Rectangular optic assembly 270x90mm – AL optic – Warm White – 24Vdc - White

**Product code**

ST03.01: Rectangular optic assembly 270x90mm – AL optic – Warm White – 24Vdc - White

Technical description

Luminaire for walkways designed to use LED lamps with a high efficiency value. Ceiling, wall-recessed and pole-mounted installation. It consists of an optical assembly with an IP66 protection rating and an outer casing or wall-mounted base to be ordered separately. The optical assembly and base are made of aluminium alloy treated with powder paint, which provides a high level of resistance to weather and UV rays. Plastic closure guard at the rear of the optical assembly. Complete with plastic cable gland and outlet cable. Transparent sodium-calcium tempered safety glass. Luminaire with no visible screws and an anti-vandal system that uses an opening key to access the rear wiring compartment (supplied in the package). All external screws used are made of A2 stainless steel.

Installation

Wall-recessed installation with a plastic outer casing to be ordered separately. Disposable polystyrene formwork for creating the outer casing housings for installations in concrete walls that are then plastered or finished with bricks so the end surface is flush with the optical assembly. Wall-mounted installation requires an aluminium base to be ordered separately. Pole-mounted installation requires a pole to be ordered separately.

Colour
White (01)

Weight (Kg)
0.45

Wiring


Version available with remote 24Vdc power supply.

Complies with EN60598-1 and pertinent regulations



IK08

IP66

**Technical data**

Im system:	975	Life Time LED 1:	100.000h - L80 - B10 (Ta 25°C)
W system:	8.3	Life Time LED 2:	100.000h - L80 - B10 (Ta 40°C)
Im source:	1710	Voltage [Vin]:	24
W source:	7.4	Lamp code:	LED
Luminous efficiency (Im/W, real value):	117.4	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	173	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	57	Intervallu temperatura ambiente:	from -30°C to 50°C.
CRI (minimum):	80	LED current [mA]:	58
Colour temperature [K]:	3000	Control:	PWM
MacAdam Step:	3		

Polar