

Last information update: May 2025

Product configuration: UG24.15

UG24.15: Linealuce - 8.1W 558.6lm - Tunable white - Grey

**Product code**

UG24.15: Linealuce - 8.1W 558.6lm - Tunable white - Grey

Technical description

Direct light linear luminaire, designed to use Tunable White (White 2700K, 4000K) LED lamps. The product can be installed using pairs of arms, ceiling/ground/wall-mounting bases, stakes, and pendant rods and cables (to be ordered separately). The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 5mm thick transparent glass screen, fixed with silicone. Complete with Tunable White (White 2700K, 4000K) multi-LED circuit. Both the 48Vdc control card (available in a DMX version and a DALI version) and the power supply must be purchased separately. Supplied with a connector with an IP68 threaded locknut. The products have a double connector (male/female) to allow pass-through wiring and continuous line applications. The product is supplied with a closure cover (UV-resistant) that covers the cables and protects against dirt and UV rays. Fitted with an Opti Beam Lens optical system with a Wall Grazing Medium optic. All external screws used are made of A2 stainless steel.

Installation

Installation accessories can be purchased separately, including arms for wall installations at a height of less than 3m, arms for wall installations at a height of more than 3m, bases for ceiling or wall-mounted installations, stakes, and pendant rods and cables.

Colour

Grey (15)

Weight (Kg)

0.76

Mounting

wall arm|wall surface|ceiling surface

Wiring

Ceiling, wall, surface, stake and pendant installation.

Notes

Supplied with a connector with an IP68 threaded locknut. The products have a double connector (male/female) to allow pass-through wiring and continuous line applications. Both the control card and power supply are remote and must be purchased separately.

Complies with EN60598-1 and pertinent regulations



IK06

IP66

**Technical data**

Im system:	559	MacAdam Step:	3
W system:	8.1	Life Time LED 1:	100,000h - L85 - B10 (Ta 25°C)
Im source:	1140	Life Time LED 2:	100,000h - L85 - B10 (Ta 40°C)
W source:	6	Voltage [Vin]:	48
Luminous efficiency (Im/W, real value):	69	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	49	Number of optical assemblies:	1
CRI (minimum):	80	Intervallo temperatura ambiente:	from -30°C to 50°C.
Rf (Colour Fidelity Index):	86	LED current [mA]:	40
Rg (Gamut Index):	96	Control:	PWM
Colour temperature [K]:	Tunable white 2700 - 4000		

	<p>CIE nL 0.49 79-93-99-100-49 UGR 16.6-18.3</p> <p>DIN A.61</p> <p>UTE 0.49B+0.00T $F^1=790$ $F^1+F^2=931$ $F^1+F^2+F^3=988$</p>
--	---