

Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 120-277VAC 50/60Hz Iout =500mA

Design iGuzzini

iGuzzini

Last information update: February 2023



Accessory code

X217: Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 120-277VAC 50/60Hz Iout =500mA

Technical description

DALI 75W dimmable electronic ballast, with STEP-DIM, ASTRO-DIM and MIDNIGHT PROFILE functions, Vin=120÷277Vac, 50÷60Hz Vout=18÷56Vdc, Iout=500mA (SELV) IP20 protection rating.

Colour
Indeterminate (00)

Weight (Kg)
0.26

Dimension (mm) (*)
133x77x39

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

Make the connections on the appropriate terminal blocks

Notes

Overvoltage protection: 8kV Common Mode, 6kV Differential Mode

Complies with EN60598-1 and pertinent regulations



IP20



Technical data

Frequency [Hz]: 47/63

Current out [mA]: 500

Inrush current: 43 A / 260 μ s

Maximum number of LED power supply units of this type per miniature circuit breaker:

B10A: 6 power supply units
B16A: 10 power supply units
C10A: 10 power supply units
C16A: 17 power supply units

Overvoltage protection:

10kV Common mode & 6kV Differential mode