

Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 220-240VAC 50/60Hz Iout =850mA

Design iGuzzini

iGuzzini

Last information update: January 2024



Accessory code

X277: Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 220-240VAC 50/60Hz Iout =850mA

Technical description

DALI 75W dimmable electronic power supply, with STEP-DIM, ASTRO-DIM and MIDNIGHT PROFILE (default) functions, Vin=220÷240 Vac, 50÷60Hz, 50÷60Hz Iout=850mA (SELV) IP20 protection rating.

Colour
Indeterminate (00)

Weight (Kg)
0.26

Dimension (mm) (*)
123x79x33

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Notes

Overvoltage protection
DALI-2 ext. -251 -252 -253

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60	Minimum dimming %:	10
Current out [mA]:	850	Overvoltage protection:	10kV Common mode & 6kV Differential mode
Inrush current:	62 A / 202 µs	Control:	DALI-2
Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 6 power supply units B16A: 10 power supply units C10A: 10 power supply units C16A: 17 power supply units		