
Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 220-240VAC 50/60Hz dimensions: 133x76x39

Design iGuzzini**iGuzzini**

Last information update: October 2023

**Accessory code**

X285: Dimmable electronic power supply unit DALI/Step-Dim/Middle of the night profile IP20 75W - VIN = 220-240VAC 50/60Hz dimensions: 133x76x39

Technical description

Constant current power supply DALI/Step-dim/Middle of the night profile IP20 75 W, 220-240Vac, 50/60Hz.

Colour
Indeterminate (00)**Weight (Kg)**
0.28**Dimension (mm) (*)**
133x76x39

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Complies with EN60598-1 and pertinent regulations

EAC**Technical data**

Frequency [Hz]: 50/60

Current out [mA]: 705

Inrush current: 54 A / - μ sMaximum number of LED power supply units of this type per miniature circuit breaker:
B10A: 7 power supply units
B16A: 12 power supply units
C10A: 12 power supply units
C16A: 20 power supply units

Minimum dimming %: 10

Overvoltage protection: 10kV Common mode & 6kV Differential mode

Control: DALI-2