

**Constant current power supply unit DALI with outgoing cables IP68 60W - VIN =110-240VAC 50/60Hz  
Iout = 1050mA dim. 180x90x68**

Last information update: July 2024



**Accessory code**

X433: Constant current power supply unit DALI with outgoing cables IP68 60W - VIN =110-240VAC 50/60Hz Iout = 1050mA dim. 180x90x68

**Technical description**

60W (1÷60W), 1050mA, DALI, IP68 electronic ballast with a high-strength thermoplastic box and outlet cables. Vin=100÷264Vac, 50÷60Hz Vout=57dc (SELV), Iout=1050mA

**Installation**

Remote installation.

**Colour**  
Indeterminate (00)

**Weight (Kg)**  
0.77

**Dimension (mm) (\*)**  
180x90x68

\* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

**Notes**

Overvoltage protection: 5kV Common mode, 4kV differenzial mode

Complies with EN60598-1 and pertinent regulations



**Technical data**

Frequency [Hz]:	50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 18 power supply units B16A: 30 power supply units C10A: 31 power supply units C16A: 51 power supply units
Current out [mA]:	1050		
Inrush current:	10 A / 200 μs		
Minimum dimming %:		1	
Overvoltage protection:		4kV Common mode & 4kV Differential mode	