

Last information update: June 2025

Product configuration: S513.15

S513.15: 47 surface Integral with side box - Neutral White - DMX - L = 1,501mm - Wall Grazing Medium optic - 63W 3780lm - 4000K - Grey

**Product code**

S513.15: 47 surface Integral with side box - Neutral White - DMX - L = 1,501mm - Wall Grazing Medium optic - 63W 3780lm - 4000K - Grey

Technical description

Direct light luminaire, designed to use monochrome LED lamps. Ceiling, wall or surface-mounted. It consists of a body and installation brackets to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in Neutral White. Supplied with a double PG13.5 and outlet cables for pass-through wiring with IP68 male/female joiners. Fitted with a PMMA diffusing filter and optics with a plastic (methacrylate) lens for Wall Grazing Medium lighting. All external screws used are made of A2 stainless steel.

Installation

Installation accessories can be purchased separately, including arms (for heights < 3m and heights > 3m) and plates.

Colour


Grey (15)

Weight (Kg)

4.45

Mounting

wall arm/wall surface



Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	3780	MacAdam Step:	3
W system:	63	Life Time LED 1:	100,000h - L80 - B10 (Ta 25°C)
Im source:	7000	Life Time LED 2:	100,000h - L80 - B10 (Ta 40°C)
W source:	52	Voltage [Vin]:	230
Luminous efficiency (Im/W, real value):	60	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	54	Number of optical assemblies:	1
CRI (minimum):	80	Intervallum temperatura ambiente:	from -30°C to 50°C.
Colour temperature [K]:	4000	Control:	DMX-RDM

Polar