


Last information update: October 2024



Product code

2168: 5 - cell Recessed luminaire - LED - Warm white - Incorporated DALI dimmable power supply - Spot optic

Technical description

rectangular miniaturised recessed luminaire with 5 optical elements with LED lamps - fixed optics - spot beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen; the structure of the optical system prevents a pinpoint effect, allowing precise, circular light distribution and emission with controlled glare. Supplied with DALI dimmable electronic control gear connected to the luminaire. Warm white high colour rendering LED.

Installation

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

Colour

White (01) | Black / Black (43) | Black / White (47)


Mounting

wall recessed/ceiling recessed

Wiring

on control gear box; screw connections with terminal block included

Complies with EN60598-1 and pertinent regulations



On the visible part of the product once installed

Technical data

lm system:	-	CRI:	90
W system:	10 (*)	Colour temperature [K]:	2700
lm source:	-	Number of lamps for optical assembly:	1
W source:	10 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1
Beam angle [°]:	12° (*)	Control:	DALI-2