

Deep Laser


Design iGuzzini

iGuzzini

Last information update: June 2023

Product configuration: MA08

MA08: medium body, Frame installation 6 LED warm white



Product code

MA08: medium body, Frame installation 6 LED warm white **Attention! Code no longer in production**

Technical description

Fixed square recessed luminaire designed to use a 6X1,5W LED lamp in warm white (3100°K) with spot optic. Recessed item with rim consisting of a single die-cast aluminium body. The upper part is a heat sink which helps to carry away the heat given off by the lamp. LED optics with a single lens made of thermoplastic material. Lamp set back 40 mm for greater visual comfort

Installation

Recessed using springs which allow easy installation in false ceilings with thickness ranging from 1 mm to 30 mm

Colour

White (01) | Grey (15)

Mounting

wall recessed|ceiling recessed

Wiring

product complete with electronic components

Complies with EN60598-1 and pertinent regulations



IP23



Technical data

lm system:	640	CRI (minimum):	80
W system:	10	Colour temperature [K]:	3000
lm source:	1000	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
W source:	8.7	Ballast losses [W]:	1.3
Luminous efficiency (lm/W, real value):	64	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	64	Number of optical assemblies:	1
Beam angle [°]:	14°		

Polar

Imax=5681 cd		Lux			
90°	180°	h	d	Em	Emax

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	56	53	51	49	53	50	50	48	75
1.0	59	56	54	52	56	54	53	51	80
1.5	63	60	58	57	59	58	57	55	86
2.0	65	63	62	60	62	61	60	58	91
2.5	66	65	64	63	64	63	62	60	94
3.0	67	66	65	64	65	64	63	62	96
4.0	68	67	66	66	66	65	64	63	98
5.0	68	68	67	67	66	66	65	63	99

Luminance curve limit

