Light Up

Design iGuzzini **iGuzzini**

Last information update: June 2024

Product configuration: ER67+X490.13
ER67: Floor-recessed Orbit luminaire D=45mm - Flush-mounted stainless steel frame - Neutral White LED - Medium Comfort optic
X490.13: Outer casing in plastic for the ground, floor with stainless steel ring + closure cap - Steel



Product code
ER67: Floor-recessed Orbit luminaire D=45mm - Flush-mounted stainless steel frame - Neutral White LED - Medium Comfort optic

Technical description
Floor or ground-recessed luminaire designed to use white monochrome LED lamps, a fixed optic and powered with a continuous current of Max 350mA. The round frame with no visible screws and the optical assembly are made of AISI 304 stainless steel with an extra-clear, sodium-calcium tempered glass cover. The luminaire is fixed to the outer casing using special locking seals that hold it in place. The unit comes complete with LED circuit, a metallized plastic OPTI BEAM reflector and honeycomb louvre. The product's wiring system features an A2 stainless steel cable gland with a 1800 mm long H05RNF type 2x1 mm² output power cable. The cable is equipped with an anti-transpiration device (IP68) that consists of a silicone-coated joint located on the power cable. An outer casing is available for installation and can be ordered separately from the plastic optic assembly. The glass unit, optical assembly, frame and outer casing together guarantee a maximum static load resistance of 2000 kg. The maximum surface temperature of the glass is less than 40°C.

Installation
The product is fixed to the outer casing using special locking seals with toolfree installation. The unit can be floor-recessed using the outer casing for installation or ground-recessed without the outer casing.

Colour	Weight (Kg)
Steel (13)* | Gold (14)* | Bronze (69)* | Burnished chrome (E6)*	0.59

* Colours on request

Mounting
Floor recessed|ground recessed

Wiring
Ballasts available: traditional and IP67 sealed 350mA. The product comes complete with a 1800 mm long H05RNF type 2x1 mm² output power cable and an electronic plate with a 350mA Max LED. Ballast to be ordered separately.

Notes
IP68 rating on both the product and the cable using IP68 connectors * The product is not suitable for installation in swimming pools and fountains. Versions with a Brass (.14), Bronze (.69) and Burnished Chrome (.E6) finish applied with PVD (Physical Vapor Deposition) coating technology on the stainless steel frame.

Complies with EN60598-1 and pertinent regulations

IK07 | 2000 kg | IP66 | 10m IP68 — Complete immersion for limited periods, not suitable for use in swimming pools or fountains.

The lighting fixtures were designed and tested to withstand a static load of up to 20000 N and to resist drive-over stress by vehicles with tires. The fixtures cannot be used in lanes subjected to horizontal stresses due to acceleration, braking and / or changes of direction.

Accessory code
X490.13: Outer casing in plastic for the ground, floor with stainless steel ring + closure cap - Steel

Technical description
Made of plastic (polypropylene). Complete with front cap, cable extraction system and twin cable entrance.

Installation
Mounted on (concrete) walls, floors and ceilings using special brackets (anchors)

Colour	Weight (Kg)
Steel (13)	0.17

Mounting
ground surface|Floor recessed|ground recessed

Complies with EN60598-1 and pertinent regulations

Technical data

lm system:	260	Colour temperature [K]:	4000
W system:	3.8	MacAdam Step:	2
lm source:	510	Life Time LED 1:	99,000h - L80 - B10 (Ta 25°C)
W source:	3.8	Life Time LED 2:	84,000h - L80 - B10 (Ta 40°C)
Luminous efficiency (lm/W, real value):	68.4	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	260	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	51	Number of optical assemblies:	1
Beam angle [°]:	22° / 21°	Intervallo temperatura ambiente:	from -25°C to 50°C.
CRI (minimum):	80	LED current [mA]:	350

Polar

Imax=1547 cd C165-345 γ=178° Lux



α=22° / 21°

h	d1	d2	Em	Emax
4	1.6	1.5	79	96
8	3.1	3	20	24
12	4.7	4.4	9	11
16	6.2	5.9	5	6