



Laser Blade XS

Design iGuzzini

iGuzzini

Last information update: October 2024



Product code

2351: Recessed Frame section 5 LEDs - integrated ON-OFF - Wall Washer Longitudinal Glare Control

Technical description

Miniaturized recessed linear luminaire for LED lamps. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient and homogeneous effect on walls from top to bottom and avoids shadow zones near the ceiling. The black polycarbonate perimeter frame is designed to significantly reduce the effect of longitudinal glare. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Flux enhancer - superpure aluminium reflector - asymmetrical textured PMMA screen. Supplied with a power supply unit connected to the luminaire. High efficiency value Neutral White LED (lm/W).

Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 24 x 96. To light walls correctly check the installation distances and centre-to-centre distances indicated on the instructions sheet.

Colour

Black / Black (43) | Black / White (47)


Mounting

ceiling recessed

Wiring

ON-OFF integrated ballast. Connection to mains network on power supply box; screw connections.

Complies with EN60598-1 and pertinent regulations



Technical data

lm system:	188 (*)	Light Output Ratio (L.O.R.) [%]:	32 (*)
W system:	10 (*)	CRI:	90
lm source:	227 (*)	Colour temperature [K]:	3500
W source:	10 (*)	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	18.0 (*)	ZVEI Code:	LED
lm in emergency mode:	-	Number of optical assemblies:	1