


Last information update: March 2025

**Product configuration: S794**

S794: Floodlight with flange - Neutral White - Remote power supply - Very Wide Flood - Class III



**Product code**

S794: Floodlight with flange - Neutral White - Remote power supply - Very Wide Flood - Class III

**Technical description**

Floodlight with LED lamp fitted with a Very Wide Flood optic. Consisting of an optical assembly made of EN1706AC 46100LF aluminium alloy and a forged steel flange for installation on cylindrical-conical poles. The optical assembly is subjected to a multi-step, pre-treatment process in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The optical assembly is fitted with a 5 mm thick tempered sodium-calcium glass cover. The product can be positioned at 330° on the vertical plane and 90° on the horizontal plane. Mechanical aiming locks for rotation on both the vertical axis and horizontal plane. The product is fitted with a 7m cable hidden inside the flange and can be installed on cylindrical-conical poles using the slots in the flange. A monochrome LED circuit is located inside the product with an Opti Beam Reflector optic system. The power supply unit is remote and needs to be ordered separately. Option of using all the optic accessories that can be mounted directly on the product or via an accessory holder frame. All external screws are made of A2 stainless steel.

**Installation**

Pole installations can be made using two M10 screws included in the end product code.

**Colour**

White (01) | Black (04) | Grey (15) | Rust Brown (F5)

**Weight (Kg)**

2.49

**Mounting**

pole-top side entry

**Notes**

Opti Beam Reflector Insulation class II Power supply unit to be ordered separately. These products can be used at a maximum ambient temperature of 50°C.

Complies with EN60598-1 and pertinent regulations



**Technical data**

Im system:	1546	Colour temperature [K]:	4000
W system:	12	MacAdam Step:	2
Im source:	1840	Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)
W source:	12	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
Luminous efficiency (Im/W, real value):	128.8	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	84	Number of optical assemblies:	1
Beam angle [°]:	78°	Intervallo temperatura ambiente:	from -30°C to 50°C.
CRI (minimum):	80	LED current [mA]:	350

**Polar**

