


Last information update: May 2025

Product configuration: QB01

QB01: Angular LED module - Frame Down LO - DALI - General Light - Neutral

**Product code**QB01: Angular LED module - Frame Down LO - DALI - General Light - Neutral **Attention! Code no longer in production****Technical description**

Angular element for Frame version profiles with contact frame; including a 4000K Neutral LED module, Low Output version. Methacrylate opal screen for diffused general light; screen set up for overlap connections. Integrated DALI control gear. Pass-through wiring for continuous lines:

Installation

Recessed using the brackets on the profile.

Colour

White (01)

Weight (Kg)

4.17

Mounting

ceiling recessed

Wiring

The angular profile is supplied with pass-through wiring for continuous lines. Quick coupling terminal blocks to simplify connections between the luminaires. LED module complete with integrated dimmable digital DALI control gear.

Notes

Take care when configuring the system; to complete a continuous line with an angular profile correctly, two initial modules are required, one for each end of the corner.

TPb rated. TPa version available on request, contact iGuzzini for more info

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

Im system:	2052	Colour temperature [K]:	4000
W system:	16.1	MacAdam Step:	3
Im source:	1350	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W source:	7.5	Lamp code:	LED
Luminous efficiency (lm/W, real value):	127.5	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	2
Light Output Ratio (L.O.R.) [%]:	76	Control:	DALI-2
CRI (minimum):	80		

Polar