


Last information update: February 2025

Product configuration: MK48

MK48: 2 - cell Recessed luminaire - LED - Warm white medium



Product code

MK48: 2 - cell Recessed luminaire - LED - Warm white medium

Technical description

rectangular miniaturised recessed luminaire with 2 optical elements with LED lamps - fixed optics - medium beam angle. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen. Connecting cable supplied. Ballast not included, available with separate code. Warm white LED.

Installation

recessed with steel wire springs for false ceilings from 1 to 20 mm thick - preparation hole 35 x 64

Colour

White (01) | Black / Black (43) | Black / White (47) | White/Gold (41)* | Grey / Black (74)* | White / burnished chrome (E7)*

Weight (Kg)

0.09

* Colours on request

Mounting

wall recessed|ceiling recessed

Wiring

direct current ballasts to be ordered separately: electronic (MXF9) for max. 7 LEDs; DALI dimmable (BZM4) for max. 20 LEDs (check instruction leaflet for compatible lengths of cables to be used)

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	374	CRI (typical):	92
W system:	4	Colour temperature [K]:	3000
Im source:	440	MacAdam Step:	3
W source:	4	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	93.5	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	85	Number of optical assemblies:	1
Beam angle [°]:	32°	LED current [mA]:	700
CRI (minimum):	90		

Polar

Imax=1184 cd	CIE nL 0.85 100-100-100-100-85 UGR <10-<10 DIN A.61 UTE 0.85A+0.00T F*1=1000 F*1+F*2=1000 F*1+F*2+F*3=1000 CIBSE LG3 L<1500 cd/m² at 65° UGR<10 L<1500 cd/mq @65°	Lux			
		h	d	Em	E _{max}
90°		1	0.6	904	1184
		2	1.1	226	296
		3	1.7	100	132
α=32°		4	2.3	56	74

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	77	73	70	68	72	70	69	67	78
1.0	80	77	74	72	76	74	73	71	83
1.5	84	81	79	78	80	79	78	75	89
2.0	87	85	83	82	84	82	81	79	93
2.5	88	87	86	85	86	85	84	81	96
3.0	89	88	88	87	87	86	85	83	98
4.0	90	90	89	89	88	88	87	84	99
5.0	91	90	90	90	89	89	87	85	100

UGR diagram

Corrected UGR values (at 440 lm bare lamp luminous flux)											
Reflect.:		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
ceiling/cav											
walls											
work pl.											
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	-2.8	-2.3	-2.6	-2.1	-1.8	-2.8	-2.3	-2.6	-2.1	-1.8
	3H	-3.0	-2.5	-2.7	-2.2	-1.9	-3.0	-2.5	-2.7	-2.2	-1.9
	4H	-3.0	-2.6	-2.7	-2.3	-2.0	-3.0	-2.6	-2.7	-2.3	-2.0
	6H	-3.1	-2.7	-2.8	-2.4	-2.1	-3.1	-2.7	-2.8	-2.4	-2.1
	8H	-3.2	-2.8	-2.8	-2.4	-2.1	-3.2	-2.8	-2.8	-2.4	-2.1
	12H	-3.2	-2.8	-2.8	-2.5	-2.1	-3.2	-2.8	-2.8	-2.5	-2.1
4H	2H	-3.0	-2.6	-2.7	-2.3	-2.0	-3.0	-2.6	-2.7	-2.3	-2.0
	3H	-3.2	-2.8	-2.8	-2.5	-2.1	-3.2	-2.8	-2.8	-2.5	-2.1
	4H	-3.3	-2.9	-2.9	-2.6	-2.2	-3.3	-2.9	-2.9	-2.6	-2.2
	6H	-3.4	-3.1	-2.9	-2.7	-2.3	-3.4	-3.1	-2.9	-2.7	-2.3
	8H	-3.4	-3.1	-3.0	-2.7	-2.3	-3.4	-3.1	-3.0	-2.7	-2.3
	12H	-3.5	-3.2	-3.0	-2.8	-2.3	-3.5	-3.2	-3.0	-2.8	-2.3
8H	4H	-3.4	-3.1	-3.0	-2.7	-2.3	-3.4	-3.1	-3.0	-2.7	-2.3
	6H	-3.5	-3.3	-3.0	-2.8	-2.4	-3.5	-3.3	-3.0	-2.8	-2.4
	8H	-3.6	-3.4	-3.1	-2.9	-2.4	-3.6	-3.4	-3.1	-2.9	-2.4
	12H	-3.6	-3.5	-3.1	-3.0	-2.5	-3.6	-3.5	-3.1	-3.0	-2.5
12H	4H	-3.5	-3.2	-3.0	-2.8	-2.3	-3.5	-3.2	-3.0	-2.8	-2.3
	6H	-3.6	-3.4	-3.1	-2.9	-2.4	-3.6	-3.4	-3.1	-2.9	-2.4
	8H	-3.6	-3.5	-3.1	-3.0	-2.5	-3.6	-3.5	-3.1	-3.0	-2.5
Variations with the observer position at spacing:											
S =	1.0H	0.9 / -25.5					0.9 / -25.5				
	1.5H	9.7 / -26.0					9.7 / -26.0				
	2.0H	11.7 / -26.8					11.7 / -26.8				