


Last information update: May 2025

**Product code**

SQ40: Luminaire with Up/Down emission L=1446 - General Light - High Output - Space Frameless optic - Neutral White – DALI-2 Sensor

Technical description

Direct (70%) / Indirect (30%) emission luminaire with Neutral White CRI90 monochrome LED lamps. Opti-Diamond (High Output) Down General Light Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Up General Light optic with opal screen. Frameless version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000. Steel pendant mount cable with millimetric adjustment system and brass component. Ceiling-mounted base in painted aluminium with galvanised steel wall plate. Product supplied with DALI dimmable electronic power supply unit positioned inside the aluminium base. Complete with lux and motion sensor DALI-2 integrated at the end of the body on the side of the base.

Installation

Pendant-mounted. Complete with power and pendant cables L=3000 with brass ceiling-fixing component. To position the luminaire correctly, taking into account the motion / daylight check function, consult the instruction manual or contact iGuzzini.

Colour

Black/Black Transparent (G1) | White/Black Transparent (M6) | Titanium/Black Transparent (Q0) | Sapphire blue/Black Transparent (Q2)

Mounting

ceiling pendant

Wiring

Product complete with DALI power supply unit positioned inside the base.

Notes

For the motion and/or daylight control function, the luminaire must be connected to a DALI-2 controller system/app and programmed for this purpose. Contact iGuzzini for the systems compatible with the DALI-2 sensor.

Complies with EN60598-1 and pertinent regulations



IP20

**Technical data**

lm system: 3993 (*)
W system: 30.7 (*)
lm source: -
W source: -
Luminous efficiency (lm/W, 130 (*)
real value):
lm in emergency mode: -

CRI: 90
Colour temperature [K]: 4000
Number of lamps for optical assembly: 1
ZVEI Code: LED
Number of optical assemblies: 1
Control: DALI-2 sensor