



Last information update: September 2024



Product code

MXL0: High recessed linear Frame profile for Ledstrip Top - L=1000

Technical description

Rigid aluminium profile with contact tab edge for recessed installation (high version); the shape of the profile allows application of all monochrome Ledstrips with front emission LEDs, available in standard version (with adhesive) or tube version (with outer sheath). Finishes available: anodised grey - white. The profile may be completed with a diffuser screen available with two finishes: opal and translucent. The raised section of the profile, coupled with the opal diffuser screen, eliminates the pinpoint effect typical of strips.

Installation

recessed in prepared milled parts; with blind milled parts direct fixing with screws (not included); the profile has a longitudinal guide to facilitate drilling. If through milled parts are present (e.g.: in plasterboard) an accessory spring kit is available (code MXP6 x 2 pcs); fix the springs on the module (centre distance and numbers depend on the length of the modules: consult the instructions leaflet), insert in the milled part prepared. Accessory closing end caps (code MXL8 - kit 2 x 5 pcs).

Colour

White (01) | Aluminium (12)

Weight (Kg)

0.27

Mounting

wall recessed|ceiling recessed|ceiling surface

Wiring

Carefully read the Ledstrip instructions sheet

Notes

Carefully read the Ledstrip instructions sheet

Complies with EN60598-1 and pertinent regulations

850°C