Design Artec Studio

Last information update: February 2025

### Product configuration: QC34

QC34: Palco single surface Ø19 - medium - remote driver

iGuzzini

### Product code

QC34: Palco single surface  $\emptyset$ 19 - medium - remote driver

### Technical description

Miniaturised adjustable spotlight for surface installation. Spotlight body with a cast zamak dissipation system and rotation unit - shaped steel fixing plate - thermoplastic surface cover base with stainless steel locking mechanism. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

#### Installation

Installation surface plate fastening - spotlight unit attached to cover base with a locking mechanism.

 Colour
 Weight (Kg)

 White (01) | Black (04)
 0.06



wall surface|ceiling surface

# Wiring

Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations















NOM-ES

Technical data			
Im system:	127	CRI (minimum):	90
W system:	2	Colour temperature [K]:	3000
Im source:	190	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W,	63.7	Lamp code:	LED
real value):		Number of lamps for optical	1
Im in emergency mode:	-	assembly:	
Total light flux at or above	0	ZVEI Code:	LED
an angle of 90° [Lm]:		Number of optical	1
Light Output Ratio (L.O.R.) [%]:	67	assemblies:	
		LED current [mA]:	700
Beam angle [°]:	24°		

## Polar

Imax=660 cd	Lux			
90° 180° 90°	h	d	Em	Emax
	1	0.4	542	660
	2	0.9	135	165
750	3	1.3	60	73
α=24°	4	1.7	34	41