


Palco Recessed / Surface

Last information update: April 2024

**Product configuration: QC34**  
QC34: Palco single surface Ø19 - medium - remote driver



**Product code**  
QC34: Palco single surface Ø19 - medium - remote driver

**Technical description**  
Miniaturised adjustable spotlight for surface installation. Spotlight body with a cast zamak dissipation system and rotation unit - shaped steel fixing plate - thermoplastic surface cover base with stainless steel locking mechanism. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort with a thermoplastic high definition lens. Ballast not included, available with separate code.

**Installation**  
Installation surface plate fastening - spotlight unit attached to cover base with a locking mechanism.

<b>Colour</b>	<b>Weight (Kg)</b>
White (01)   Black (04)	0.06

**Mounting**  
wall surface|ceiling surface

**Wiring**  
Output cables for connecting to power supply line.

Complies with EN60598-1 and pertinent regulations



Technical data			
Im system:	127	CRI (minimum):	90
W system:	2	Colour temperature [K]:	3000
Im source:	190	MacAdam Step:	2
W source:	2	Life Time LED 1:	> 50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	63.7	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	67	Number of optical assemblies:	1
Beam angle [°]:	24°	LED current [mA]:	700

