

**Constant current power supply unit DALI with outgoing cables IP68 15W - VIN =110-240VAC 50/60Hz
Iout = 350mA dim. 180x90x68**

Design iGuzzini

iGuzzini

Last information update: January 2025



Accessory code

X212: Constant current power supply unit DALI with outgoing cables IP68 15W - VIN =110-240VAC 50/60Hz Iout = 350mA dim. 180x90x68

Technical description

15W (0÷15W), 350mA, DALI, IP68 electronic ballast with a high-strength thermoplastic box and outlet cables. Vin=90÷264Vac, 50÷60Hz Vout=47Vdc (SELV), Iout=350mA

| Colour | Weight (Kg) | Dimension (mm) (*) |
|---|-------------|--------------------|
| Indeterminate (00) | 0.77 | 170x90x70 |
| * The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed. | | |

Wiring

Make the connections on the appropriate terminal blocks

Notes

Overvoltage protection: 4kV Common Mode, 3.5kV Differential Mode

Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|-------------------------|-------------|--|--|
| Frequency [Hz]: | 50/60 | Maximum number of LED power supply units of this type per miniature circuit breaker: | B10A: 31 power supply units B16A: 50 power supply units C10A: 52 power supply units C16A: 85 power supply units |
| Current out [mA]: | 350 | | |
| Inrush current: | 5 A / 50 µs | | |
| Minimum dimming %: | | 1 | |
| Overvoltage protection: | | 4kV Common mode & 3kV Differential mode | |