

**Constant current power supply unit DALI with outgoing cables IP68 15W - VIN =110-240VAC 50/60Hz
Iout = 350mA dim. 180x90x68**

Design iGuzzini

iGuzzini

Last information update: February 2023



Accessory code

X212: Constant current power supply unit DALI with outgoing cables IP68 15W - VIN =110-240VAC 50/60Hz Iout = 350mA dim. 180x90x68

Technical description

15W (0÷15W), 350mA, DALI, IP68 electronic ballast with a high-strength thermoplastic box and outlet cables. Vin=90÷264Vac, 50÷60Hz Vout=47Vdc (SELV), Iout=350mA

Colour	Weight (Kg)	Dimension (mm) (*)
Indeterminate (00)	0.77	170x90x70

* The dimensions may change according to production requirements to ensure that performance levels and installation methods are observed.

Wiring

Make the connections on the appropriate terminal blocks

Notes

Overvoltage protection: 4kV Common Mode, 3.5kV Differential Mode

Complies with EN60598-1 and pertinent regulations



Technical data

Frequency [Hz]:	50/60	Maximum number of LED power supply units of this type per miniature circuit breaker:	B10A: 31 power supply units B16A: 50 power supply units C10A: 52 power supply units C16A: 85 power supply units
Current out [mA]:	350	Minimum dimming %:	1
Inrush current:	5 A / 50 µs	Overvoltage protection:	4kV Common mode & 3kV Differential mode