



Last information update: May 2025

Product configuration: QX66

QX66: Minimal 1 cell - Flood - LED

**Product code**

QX66: Minimal 1 cell - Flood - LED

Technical description

Square miniaturised recessed luminaire for a single LED lamp - fixed optic. Die-cast aluminium body, minimal version (frameless) installed flush with ceiling. For recessed installation in a false ceiling a specific adapter is required that is available with a separate item code. Metallised, thermoplastic, high definition OptiBeam reflector, integrated in a set-back position in the anti-glare screen. Connecting cable supplied. Ballast not included, available with separate code.

Installation

The recess body is inserted in the specific adapter installed previously by means of a steel wire spring - check the thickness of the false ceiling and use a compatible frame available with a separate item code.

Colour

White (01) | Black (04)

Weight (Kg)

0.05

Mounting

wall recessed|ceiling recessed|ceiling surface

Wiring

Constant current ballasts to be ordered separately: ON-OFF - code no. MXF9; DALI dimmable - code no. BZM4 - check the instruction sheet for the operating current setting and the compatible length and cross sections of the cables to be used.

Complies with EN60598-1 and pertinent regulations



IP20

IP23

On the visible part of the product once installed

**Technical data**

lm system:	179	CRI (typical):	92
W system:	2	Colour temperature [K]:	2700
lm source:	210	MacAdam Step:	3
W source:	2	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Luminous efficiency (lm/W, real value):	89.3	Lamp code:	LED
lm in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	85	Number of optical assemblies:	1
Beam angle [°]:	32°	LED current [mA]:	700
CRI (minimum):	90		

Polar

Imax=565 cd		CIE		Lux			
90°	180°	nL 0.85	100-100-100-100-85	h	d	Em	Emax
		UGR <10-10	DIN A.61	1	0.6	431	565
		UTE 0.85A+0.00T	F*1=1000	2	1.1	108	141
		F*1+F*2=1000	F*1+F*2+F*3=1000	3	1.7	48	63
		CIBSE LG3 L<1500 cd/m² at 65°	UGR<10 L<1500 cd/mq @65°	4	2.3	27	35
α=32°							

Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	77	73	70	68	72	70	69	67	78
1.0	80	77	74	72	76	74	73	71	83
1.5	84	81	79	78	80	79	78	75	89
2.0	87	85	83	82	84	82	81	79	93
2.5	88	87	86	85	86	85	84	81	96
3.0	89	88	88	87	87	86	85	83	98
4.0	90	90	89	89	88	88	87	84	99
5.0	91	90	90	90	89	89	87	85	100

UGR diagram

Corrected UGR values (at 210 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim											
x	y										
2H	2H	-3.0	-2.5	-2.7	-2.2	-2.0	-3.0	-2.5	-2.7	-2.2	-2.0
	3H	-3.1	-2.6	-2.8	-2.4	-2.1	-3.1	-2.6	-2.8	-2.4	-2.1
	4H	-3.2	-2.8	-2.9	-2.5	-2.2	-3.2	-2.8	-2.9	-2.5	-2.2
	6H	-3.3	-2.9	-2.9	-2.6	-2.2	-3.3	-2.9	-2.9	-2.6	-2.2
	8H	-3.3	-2.9	-3.0	-2.6	-2.3	-3.3	-2.9	-3.0	-2.6	-2.3
	12H	-3.4	-3.0	-3.0	-2.6	-2.3	-3.4	-3.0	-3.0	-2.6	-2.3
4H	2H	-3.2	-2.8	-2.9	-2.5	-2.2	-3.2	-2.8	-2.9	-2.5	-2.2
	3H	-3.4	-3.0	-3.0	-2.6	-2.3	-3.4	-3.0	-3.0	-2.6	-2.3
	4H	-3.4	-3.1	-3.0	-2.7	-2.4	-3.4	-3.1	-3.0	-2.7	-2.4
	6H	-3.5	-3.2	-3.1	-2.8	-2.4	-3.5	-3.2	-3.1	-2.8	-2.4
	8H	-3.6	-3.3	-3.1	-2.9	-2.5	-3.6	-3.3	-3.1	-2.9	-2.5
	12H	-3.6	-3.4	-3.2	-3.0	-2.5	-3.6	-3.4	-3.2	-3.0	-2.5
8H	4H	-3.6	-3.3	-3.1	-2.9	-2.5	-3.6	-3.3	-3.1	-2.9	-2.5
	6H	-3.7	-3.5	-3.2	-3.0	-2.5	-3.7	-3.5	-3.2	-3.0	-2.5
	8H	-3.7	-3.5	-3.2	-3.1	-2.6	-3.7	-3.5	-3.2	-3.1	-2.6
	12H	-3.8	-3.6	-3.3	-3.1	-2.6	-3.8	-3.6	-3.3	-3.1	-2.6
12H	4H	-3.6	-3.4	-3.2	-3.0	-2.5	-3.6	-3.4	-3.2	-3.0	-2.5
	6H	-3.7	-3.5	-3.2	-3.1	-2.6	-3.7	-3.5	-3.2	-3.1	-2.6
	8H	-3.8	-3.6	-3.3	-3.1	-2.6	-3.8	-3.6	-3.3	-3.1	-2.6
Variations with the observer position at spacing:											
S =		1.0H	0.9 / -25.5				0.9 / -25.5				
		1.5H	9.7 / -26.0				9.7 / -26.0				
		2.0H	11.7 / -26.8				11.7 / -26.8				