


Last information update: February 2025

Product configuration: 649A

649A: SIPARIO Ø122 spotlight - DALI - Medium - OBReflector -

**Product code**

649A: SIPARIO Ø122 spotlight - DALI - Medium - OBReflector -

Technical description

Ø122 adjustable spotlight with adapter for installation on a base or electrified track. LED lamp with C.O.B. (Chip on board) technology, -CRI97- high colour rendering and 4000K tone.

Die-cast aluminium body with thermoplastic rear cap and front ring (Mass-Balance). The product can be rotated by 360° around the vertical axis with a mechanical lock and tilted by 90° relative to the horizontal plane. Passive heat dissipation.

OptiBeam Reflector optical system with Medium optic. Anti-scratch reflector made of P.V.D. (Physical Vapour Deposition) aluminium that can provide optimum performance in terms of light efficiency.

Dimmable electronic DALI-2 power supply integrated in the body of the luminaire.

Spotlight with Push&Go system designed to facilitate and safely accelerate the connection between product and optic accessory.

Mechanically disconnecting the accessory allows it to be disengaged but not dropped. Three internal accessories and one external one can be used simultaneously. All internal accessories rotate 360° about the spotlight longitudinal axis.

Installation

Base or mains voltage track.

Colour

White (01) | Matte black (V0)

Weight (Kg)

1.45

Mounting

three circuit track

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	3136	MacAdam Step:	2
W system:	34.9	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
Im source:	4020	Lamp code:	LED
W source:	30	Number of lamps for optical assembly:	1
Luminous efficiency (Im/W, real value):	89.8	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	78	Minimum dimming %:	1
Beam angle [°]:	19°	Overvoltage protection:	2kV Common mode & 1kV Differential mode
CRI (minimum):	97	Control:	DALI-2
Colour temperature [K]:	4000		

Polar