Design iGuzzini

iGuzzini

Last information update: May 2025

Product configuration: Q919.43

Q919.43: Linear module LB XS for 48V track - Wall Washer - 18.4W 589lm - 2700K - CRI 90 - Black / Black



184

Product code

Q919.43: Linear module LB XS for 48V track - Wall Washer - 18.4W 589lm - 2700K - CRI 90 - Black / Black

Technical description

Fixed linear Wall Washer module complete with adapter for installation on a 48V low voltage track. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each light module on the track to be adjusted separately. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an even efficient beam on the wall. Extruded aluminium main body and technical dissipation unit. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

Installation

Mechanical fastening with adapter on track.

Colour Weight (Kg) Black / Black (43) 0.32



Low voltage track

Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

Complies with EN60598-1 and pertinent regulations

8















27

50

Technical data Im system: 589 W system: 18.4 1550 Im source: W source: 17 Luminous efficiency (lm/W, 32 real value): Im in emergency mode: Total light flux at or above an angle of 90° [Lm]: Light Output Ratio (L.O.R.) 38 [%]: 90

CRI (minimum): Rf (Colour Fidelity Index): 92 Rg (Gamut Index): 102 Colour temperature [K]: 2700 MacAdam Step: LED current [mA]: Power factor: Control:

Life Time LED 1: > 50,000h - L80 - B10 (Ta 25°C) LED Lamp code: Number of lamps for optical 1 assembly: ZVEI Code: LED Number of optical assemblies:

600 See installation instructions Minimum dimming %: Overvoltage protection: 2kV Common mode & 1kV

Differential mode CCR Dimming mode: DALI

Polar

C5-185 γ=15°	Lux				
180° 90°	h	d1	d2	Em	Emax
	1	1	1.5	239	405
	2	2	3	60	101
	3	3	4.5	27	45
0°	4	4	6	15	25
	180° 90°	1 2 3	180° 90° h d1 1 1 2 2 3 3	180° 90° h d1 d2 1 1 1.5 2 2 3 3 3 4.5	180° 90° h d1 d2 Em 1 1 1.5 239 2 2 3 60 3 3 4.5 27

