

Last information update: May 2025



Product code

QY75: Superrail 48V (16A) surface-mounted/pendant DOWN track - L 2000

Technical description

New 48V (16A) low voltage Superrail track for ceiling, wall and pendant installations. Designed for installing lighting elements supplied with a 48V (16A) adapter (for some lighting elements a new adapter must be ordered separately). In the pendant version this can be installed in the UP part of the relevant LED STRIP module. Made of painted extruded aluminium. The integrated DALI converter circuit, designed to interact with the DC/DC driver included in the spot adapters, allows the lighting elements inserted in the track to be programmed individually. To obtain continuous lines, direct and corner joints are available with separate codes. Accessory installation systems with separate codes. Sealing sheath available for positioning flush with the track opening.

Installation

Ceiling, wall or pendant mounted.

Colour

White (01) | Black (04)

Weight (Kg)

2.1


Mounting

wall surface|ceiling surface|ceiling pendant

Wiring

The DALI converter, designed for remote installation, is available with a separate code. For maximum load details and cabling procedures see the instruction sheet.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	-	Luminous efficiency (lm/W, 0
W system:	-	real value):
Im source:	-	Im in emergency mode: -
W source:	-	Number of optical assemblies: 0