Design Artec Studio

iGuzzini

Last information update: April 2025

Product configuration: QG71

QG71: Warm white medium body spotlight - DALI ballast - medium optic



Product code


QG71: Warm white medium body spotlight - DALI ballast - medium optic

Technical description

Adjustable spotlight with adapter for installation on DALI track for high output LED lamp with monochrome emission in a warm White (3,000K) tone. DALI ballast integrated in the product. Luminaire made of die-cast aluminium and thermoplastic material, allows 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. The luminaire has mechanical aiming locks for both movements, operated using the same tool on two screws, one at the side of the rod and one on the adapter for the track. Passive heat dissipation. Reflector in superpure mirrored aluminium with special faceting that improves the distribution of the light beam (OPTIBEAM). Spotlight can hold up to two flat accessories at the same time. Another external component can also be applied, selected from directional flaps and an anti-glare screen. All external accessories rotate 360° about the spotlight longitudinal axis.

Installation

On a DALI electrified track



Colour

White (01) | Black (04)

Weight (Kg)

2.1

Mounting

dali track|wall surface|ceiling surface

Wiring

DALI components housed in the luminaire

Sistemi_di_controllo_compatibili:

Quick BLE & Quick DALI - Touch display 7" &

Quick DALI LMS Quick & Master Pro Evo KNX &



















Complies with EN60598-1 and pertinent regulations

11 **20**

Technical	data

Im system:	2916	CRI (minimum):	97	
W system:	41.7	Colour temperature [K]:	3000	
Im source:	3750	MacAdam Step:	2	
W source:	36	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)	
Luminous efficiency (lm/W,	69.9	Lamp code:	LED	
real value):		Number of lamps for optical	1	
Im in emergency mode:	-	assembly:		
Total light flux at or above	0	ZVEI Code:	LED	
an angle of 90° [Lm]:		Number of optical	1	
Light Output Ratio (L.O.R.) 78		assemblies:		
[%]:		Control:	DALI-2	
Beam angle [°]:	18°			

Polar

Imax=19447 cd	Lux			
90° 180° 90°	h	d	Em	Emax
	2	0.6	3665	4862
	4	1.2	916	1215
20000	6	1.8	407	540
α=17°	8	2.4	229	304