iGuzzini

Last information update: November 2024

## Product configuration: P878

P878: Pole-mounted system - Large body optical assembly - Neutral White - ST1 street optic.




## Product code

P878: Pole-mounted system - Large body optical assembly - Neutral White - ST1 street optic.

## Technical description

Outdoor luminaire with direct light street optic, designed to use LED lamps. The optical assembly is made of EN1706AC 46100LF aluminium alloy and subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and an acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. With a 5 mm thick tempered sodium-calcium glass cover. When pole-mounted the product can be adjusted by +15°/-5° and +5°/-15 when side-mounted. High visual comfort. Polymer optic lenses offering high yield and even light distribution. Complete with circuit fitted with Neutral White monochrome power LEDs. Extractable control gear connected with quick-coupling connectors. 220-240V ac 50/60Hz DALI electronic ballast. The optical assembly is fixed to the ceiling or pole-top attachment by two fixing screws. The light flow emitted in the upper hemisphere of the system in the horizontal position is null (in conformity with the strictest standards for the prevention of light pollution). All external screws are made of stainless steel.



## Installation

The floodlight can be installed on the pole-top with a die-cast aluminium single/double attachment for ø60/76/102/120mm poles or a triple attachment for ø102/120 mm poles. Side die-cast aluminium attachment for tapered poles with diameters between ø 46 and ø76.

Colour White (01)   Black (04)   Grey (15)   Rust Brown (F5)	Weight (Kg) 8.3
Mounting wall arm pole arm pole-top side entry pole-top	
	ush in terminal board. Resistance to mains voltage spikes of up to y point is guaranteed by a nickel-plated brass M24x1.5 cable clamp,

suitable for cables with a max external 16mm  $\phi$  (1,5-2.5mm<sup>2</sup> cross section).

 						Co	mplies with	h EN60598-	1 and pertin	ent regulation
IK08	IP66	CE	UK CA	Æ.	8	EAC			Ŵ	©

Technical data					
Im system:	7980	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)		
W system:	57.9	Lamp code:	LED		
Im source:	-	Number of lamps for optical	1		
W source:	-	assembly:			
Luminous efficiency (Im/W,	137.8	ZVEI Code:	LED		
real value):		Number of optical	1		
Im in emergency mode:	-	assemblies:			
Total light flux at or above an angle of 90° [Lm]:	0	Intervallo temperatura ambiente:	from -40°C to 50°C.		
Light Output Ratio (L.O.R.)	100	Power factor:	See installation instructions		
[%]:			62 A / 202 μs		
CRI (minimum):	70	Maximum number of			
Colour temperature [K]:	4000	luminaires of this type per	B10A: 6 luminaires B16A: 10 luminaires		
MacAdam Step:	5	miniature circuit breaker:			
ife Time LED 1: 100,000h - L90 - B10 (Ta 25°			C10A: 10 luminaires C16A: 17 luminaires		
		Minimum dimming %:	10		
		Overvoltage protection:	10kV Common mode & 6kV Differential mode		
		Control:	DALI-2		

