iGuzzini

Last information update: May 2024

Product configuration: MD47+L061

MD47: Spotlight - Large body - 70W HIT-CE - Electronic ballast - Medium Optic






Technical description

Adjustable spotlight with adapter for installation on a mains voltage track. Luminaire made of die-cast aluminium. Spotlight double adjustability allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. Mechanical aiming locks both for rotation about the vertical axis and tilting relative to the horizontal plane. Equipped with electronic ballast. An external component may be applied, such as directional flaps with 360° rotation and which can be fully closed. Luminaire supplied withmedium optic 70W HIT G12 IP 40 on the optical assembly.

Installation Installation on electrified tracks.

installation on electrilled track

Colour White (01) | Black (04) | Grey / Black (74)



Mounting three circuit track

Wiring Electronic components for discharge lamp housed in the body



Complies with EN60598-1 and pertinent regulations

Technical data			
Im system:	4394.9	CRI:	92
W system:	78	Colour temperature [K]:	4200
Im source:	6600	Voltage [Vin]:	230
W source:	70	Lamp code:	L061
Luminous efficiency (Im/W,	56.3	Socket:	G12
real value):		Number of lamps for optical	1
Im in emergency mode:	-	assembly:	
· • • • • • • • • • • • • • • • • • • •	0	ZVEI Code:	HIT-CE
an angle of 90° [Lm]:		Number of optical	1
Light Output Ratio (L.O.R.) [%]:	67	assemblies:	
Beam angle [°]:	16°		

Polar

