



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO.: 2016011001898340

Valid from: Jul.03,2023

Valid until: Aug.30,2026

NAME AND REGISTERED ADDRESS OF THE APPLICANT iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

NAME AND REGISTERED ADDRESS OF THE MANUFACTURER iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

NAME AND LOCATION OF THE FACTORY iGuzzini illuminazione S.p.A.
Via Mariano Guzzini, 37 62019 Recanati, Italy

PRODUCT MODEL(S) Recessed Luminaires For LED Modules (Controlled Port Dimming, Ceiling Recessed, A.C. Supplied Electronic Controlgear For LED Modules, Class I , IP20, Suitable For Direct Mounting On Normally Flammable Material, Not Covered By Insulating Material)
See Appendix. 220/240V ~ 50/60Hz, The maximum total current for looping-in is 9A.

STANDARDS AND TECHNICAL REQUIREMENTS GB/T 17743-2021;GB 7000.1-2015;GB 7000.202-2008

This is to certify that the above mentioned product(s) complies with the requirements of implementation rules for compulsory certification(REFNO. CNCA-C10-01:2014)

The validity of the certificate is subject to positive result of the regular follow up inspection by issuing certification body until the expiry date.

Date of original issued: Aug.31,2016

Accredited by China National Accreditation Service for Conformity Assessment CNAS C001-P

The certificate information is available through the QR code below or CNCA's website: www.cnca.gov.cn



SIGNATURE:

谢肇煦



CHINA QUALITY CERTIFICATION CENTRE



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

CERTIFICATE NO. : 2016011001898340

page 1 of 1

paper:

This certificate and attachments shall be used at the same time, and the verification instructions can be found in the main certificate.

控制端口调光 (DALI 调光):

N371 12.6W(36×0.3W/LED), N373 12.6W(36×0.3W/LED), QB33 23.2W(128×0.17W/LED),
QB35 23.2W(128×0.17W/LED), QB37 23.2W(128×0.17W/LED), QB39 23.2W(128×0.17W/LED),
QB46 23.2W(128×0.17W/LED), QB54 23.2W(128×0.17W/LED), QB13 12.8W(48×0.23W/LED),
QB21 12.8W(48×0.23W/LED), QB44 12.6W(64×0.17W/LED), QB52 12.6W(64×0.17W/LED),
QC06 15.2W(192×0.07W/LED), QC10 15.2W(192×0.07W/LED), QB45 18.5W(96×0.17W/LED),
QB53 18.5W(96×0.17W/LED), QB01 16.7W(64×0.23W/LED), QB03 16.7W(64×0.23W/LED),
QB05 16.7W(64×0.23W/LED), QB07 16.7W(64×0.23W/LED), QB14 16.7W(64×0.23W/LED),
QB22 16.7W(64×0.23W/LED), QB12 8.9W(32×0.23W/LED), QB20 8.9W(32×0.23W/LED),
QB81 10.5W(128×0.07W/LED), QB83 10.5W(128×0.07W/LED), QB85 10.5W(128×0.07W/LED),
QB87 10.5W(128×0.07W/LED), QB92 5.8W(64×0.07W/LED), QB93 8.2W(96×0.07W/LED),
QB94 10.5W(128×0.07W/LED), QC00 5.8W(64×0.07W/LED), QC01 8.2W(96×0.07W/LED),
QC02 10.5W(128×0.07W/LED), Q447 10.5W(2×(32×0.11W/LED)), Q453 10.5W(2×(32×0.11W/LED)),
Q448 16W(3×(32×0.11W/LED)), Q454 16W(3×(32×0.11W/LED)), Q437 21W(4×(32×0.12W/LED)),
Q439 21W(4×(32×0.12W/LED)), Q441 21W(4×(32×0.12W/LED)), Q443 21W(4×(32×0.12W/LED)),
Q449 21W(4×(32×0.12W/LED)), Q455 21W(4×(32×0.12W/LED)), Q407 22W(2×(32×0.28W/LED)),
Q413 22W(2×(32×0.28W/LED)).

220/240V~ 50/60Hz。通过式布线最大电流 9A。



CHINA QUALITY CERTIFICATION CENTRE



中国国家强制性产品认证证书

证书编号: 2016011001898340

发证日期: 2023年07月03日
有效期至: 2026年08月30日

认证委托人名称 及注册地址	iGuzzini illuminazione S.p.A. Via Mariano Guzzini, 37 62019 Recanati, 意大利
产品生产者名称 及注册地址	iGuzzini illuminazione S.p.A. Via Mariano Guzzini, 37 62019 Recanati, 意大利
生产企业名称 及生产地址	iGuzzini illuminazione S.p.A. Via Mariano Guzzini, 37 62019 Recanati, 意大利
产品名称和系列、 规格、型号	嵌入式灯具(控制端口调光, 嵌天花板式, LED 模块用交流电子控制装置, I类, IP20, 适宜直接安装在普通可燃材料表面, 不能被隔热材料覆盖) 见附件。220/240V~ 50/60Hz, 通过式布线最大电流 9A.
产品标准和 技术要求	GB/T 17743-2021;GB 7000.1-2015;GB 7000.202-2008

上述产品符合 CNCA-C10-01:2014 认证规则的要求, 特发此证。
证书有效期内本证书的有效性依据发证机构的定期监督获得保持。
本证书为变更证书, 证书首次颁发日期: 2016年08月31日
经中国合格评定国家认可委员会认可 CNAS C001-P

可通过扫描下方二维码或登录国家认监委网站(www.cnca.gov.cn)查验证书信息



签发:

谢肇煦



中国质量认证中心



中国国家强制性产品认证证书

证书编号：2016011001898340

第 1 页 / 共 1 页

本证书及附件应同时使用，信息查验说明见证书页

纸号：

控制端口调光 (DALI 调光):

N371 12.6W(36×0.3W/LED), N373 12.6W(36×0.3W/LED), QB33 23.2W(128×0.17W/LED),
QB35 23.2W(128×0.17W/LED), QB37 23.2W(128×0.17W/LED), QB39 23.2W(128×0.17W/LED),
QB46 23.2W(128×0.17W/LED), QB54 23.2W(128×0.17W/LED), QB13 12.8W(48×0.23W/LED),
QB21 12.8W(48×0.23W/LED), QB44 12.6W(64×0.17W/LED), QB52 12.6W(64×0.17W/LED),
QC06 15.2W(192×0.07W/LED), QC10 15.2W(192×0.07W/LED), QB45 18.5W(96×0.17W/LED),
QB53 18.5W(96×0.17W/LED), QB01 16.7W(64×0.23W/LED), QB03 16.7W(64×0.23W/LED),
QB05 16.7W(64×0.23W/LED), QB07 16.7W(64×0.23W/LED), QB14 16.7W(64×0.23W/LED),
QB22 16.7W(64×0.23W/LED), QB12 8.9W(32×0.23W/LED), QB20 8.9W(32×0.23W/LED),
QB81 10.5W(128×0.07W/LED), QB83 10.5W(128×0.07W/LED), QB85 10.5W(128×0.07W/LED),
QB87 10.5W(128×0.07W/LED), QB92 5.8W(64×0.07W/LED), QB93 8.2W(96×0.07W/LED),
QB94 10.5W(128×0.07W/LED), QC00 5.8W(64×0.07W/LED), QC01 8.2W(96×0.07W/LED),
QC02 10.5W(128×0.07W/LED), Q447 10.5W(2×(32×0.11W/LED)), Q453 10.5W(2×(32×0.11W/LED)),
Q448 16W(3×(32×0.11W/LED)), Q454 16W(3×(32×0.11W/LED)), Q437 21W(4×(32×0.12W/LED)),
Q439 21W(4×(32×0.12W/LED)), Q441 21W(4×(32×0.12W/LED)), Q443 21W(4×(32×0.12W/LED)),
Q449 21W(4×(32×0.12W/LED)), Q455 21W(4×(32×0.12W/LED)), Q407 22W(2×(32×0.28W/LED)),
Q413 22W(2×(32×0.28W/LED)).

220/240V~ 50/60Hz。通过式布线最大电流 9A。



中国质量认证中心