

View Opti Beam Lens round


Design iGuzzini /
Arup

iGuzzini

Last information update: March 2025

Product configuration: 207B

207B: 48V round spotlight - Ø 126 small body - Wall Washer - BLE Casambi



Product code

207B: 48V round spotlight - Ø 126 small body - Wall Washer - BLE Casambi

Technical description

Adjustable spotlight with adapter for installation on 48V low voltage track. Luminaire made of die-cast aluminium with a front part in a thermoplastic material. The adapter made of a thermoplastic material includes the DC/DC driver circuit and Bluetooth protocol. Integrated «Bluetooth Casambi» technology allows each light module inserted on the track to be adjusted independently. Bluetooth Low Energy (Casambi) technology. Frequency 2.4 GHz BLE. The luminaire can be controlled with the Casambi App that enables on-off, dimming and scene recall functions. The app is available on the Apple Store and Google Play Store. It can be integrated in the system's "Mesh" network that allows multiple luminaires to be controlled. OTA (over the air) update via app. Integrated Beacon that can be activated via Smart Light Control (iBeacon) that enables functions including push notification and indoor navigation-wayfinding. The double adjustability of the spotlight allows a 360° rotation about the vertical axis and 90° tilting relative to the horizontal plane. A rapid tool-free system for connecting the adapter electrically and mechanically to the track. Optical assembly with OPTIBEAM LENS technology designed to create homogeneous, sharply defined vertical illumination on vertical surfaces. When combined with accessory item code. MZ16 (asymmetrical visor) light emission is further optimised on the wall.

Installation

An adapter is used to fix the device mechanically and tool-free to the 48V track. Max luminaire-luminaire distance (*): 8 m; max smartphone-luminaire distance (*): 20 m.

Colour

Black (04) | Black / White (47)

Weight (Kg)

1.07

Mounting

Low voltage track

Wiring

Direct connection on 48V track. Track power supply unit to be ordered separately. Luminaire that can be controlled with Bluetooth technology (Casambi).

Notes

(*) The maximum distance for Bluetooth installations is affected by physical obstacles, like walls, metal panels and the layout of the system. We suggest that a test is conducted at the installation site. Technical and anti-glare accessories available; with option of the combined installation of two internal accessories.

Complies with EN60598-1 and pertinent regulations



Technical data

Im system:	1552	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	19.1	Voltage [Vin]:	48
Im source:	2250	Lamp code:	LED
W source:	18	Number of lamps for optical assembly:	1
Luminous efficiency (lm/W, real value):	81.3	ZVEI Code:	LED
Im in emergency mode:	-	Number of optical assemblies:	1
Total light flux at or above an angle of 90° [Lm]:	0	LED current [mA]:	500
Light Output Ratio (L.O.R.) [%]:	69	Power factor:	See installation instructions
CRI (minimum):	90	Minimum dimming %:	1
Colour temperature [K]:	3500	Control:	Casambi
MacAdam Step:	2		

Polar

Imax=3220 cd C0-180 γ=12° Lux					
90°	180°	90°	h	d1	d2 Em Emax
			4	1.9	3.4 106 189
			8	3.8	6.8 26 47
			12	5.7	10.2 12 21
			16	7.6	13.6 7 12
α = 27° / 46°					

Isolux

