

## Libera Stand-alone

Design Artec  
Studio

iGuzzini

Last information update: May 2025

### Product configuration: SJ76(BR)

SJ76: Linear pendant Up/Down luminaire L=1428 - General Light - High Output - Space Frameless optic -



### Product code

SJ76: Linear pendant Up/Down luminaire L=1428 - General Light - High Output - Space Frameless optic -

### Technical description

Direct (70%) / Indirect (30%) emission luminaire with CRI90 monochrome LED lamps. Opti-Diamond (High Output) Down General Light Space optic available in a White Cover (Transparent white) or Black Cover (Transparent black) version. Up General Light optic with opal screen. Frameless version extruded aluminium profile with die-cast zamak end caps. Complete with power and pendant cable L=3000 that can be adjusted as required. Steel pendant mount cable with millimetric adjustment system and brass component. Complete with 48Vdc Mid-Power Led circuit and DALI dimming system. "Powerline" technology allows each product connected to the system to be adjusted separately.

### Installation

A tool-free system for connecting the product electrically and mechanically to the 48V Filorail low voltage track.

### Colour

White/White Transparent (G0) | Black/Black Transparent (G1) |  
Black/White Transparent (G2) | White/Black Transparent (M6) |  
Titanium/White Transparent (P9) | Titanium/Black Transparent  
(Q0) | Sapphire blue/White Transparent (Q1) | Sapphire  
blue/Black Transparent (Q2)

### Weight (Kg)

1.14

### Mounting

ceiling pendant


### Wiring

Power supply unit (48V) to be ordered separately as specified in the instruction sheet.

Complies with EN60598-1 and pertinent regulations



IP20



### Technical data

Im system:	3420.0	MacAdam Step:	3
W system:	30.6	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
Im source:	4560	Voltage [Vin]:	48
W source:	29	Lamp code:	LED
Luminous efficiency (Im/W, real value):	111.76	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	1257.53	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	75	Power factor:	See installation instructions
Beam angle [°]:	61°	Overvoltage protection:	0kV Common mode & 0kV Differential mode
CRI:	90	Control:	DALI
Colour temperature [K]:	2700		