


Product configuration: 843A.01

843A.01: Floodlight with box – Warm White – Integrated power supply - Zhaga Ready - 39.9W 3954.6lm - 2200K - White



843A.01: Floodlight with box – Warm White – Integrated power supply - Zhaga Ready - 39.9W 3954.6lm - 2200K - White

Floodlight designed to use LED lamps and a Flood optic. Consisting of an optical assembly, an arm with a swivel joint, a glass-holding frame and a power supply box in aluminium alloy, subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozincation and sealing. The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. Transparent, 4mm thick, tempered sodium-calcium closing glass. The gasket is in black silicone. The product includes an Opti Beam Lens optical system complete with a Warm White monochrome LED circuit. The electronic DALI-2 power supply is integrated in the product and compatible with remote management systems. The frame includes steel retaining cables. The product is connected to the power supply box via a Ø12mm diameter stainless steel braided metal cable. The power supply box is fitted with a multi-pole Zhaga 4 Pin socket. The product can be adjusted on a vertical plane by ±45° and on a horizontal plane by 360°. All external screws used are made of A2 stainless steel.

The product can be ground-installed (using code 1173 and 0456 accessories, to be purchased separately) and wall-mounted (using the code 1172 accessory, to be purchased separately).

Colour	Weight (Kg)
White (01)	6.07

wall surface|free standing

Complies with EN60598-1 and pertinent regulations



Im system:	3955	MacAdam Step:	3
W system:	39.9	Life Time LED 1:	100,000h - L90 - B10 (Ta 25°C)
Im source:	5070	Life Time LED 2:	100,000h - L90 - B10 (Ta 40°C)
W source:	36	Lamp code:	LED
Luminous efficiency (Im/W, real value):	99.1	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	0	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	78	Intervallo temperatura ambiente:	from -20°C to +35°C. (*)
Beam angle [°]:	29°	Power factor:	See installation instructions
CRI (minimum):	80	Inrush current:	24.6 A / 160 µs
Rf (Colour Fidelity Index):	85	Maximum number of luminaires of this type per miniature circuit breaker:	B10A: 18 luminaires B16A: 30 luminaires C10A: 31 luminaires C16A: 51 luminaires
Rg (Gamut Index):	95		
Colour temperature [K]:	2200	Minimum dimming %:	10
		Overvoltage protection:	10kV Common mode & 6kV Differential mode

* Preliminary data
