

Last information update: May 2025

Product configuration: Q423+QH94
QH94: Plate - Down - Office / Working UGR < 19 - DALI - Neutral LED - L 3588



Product code
QH94: Plate - Down - Office / Working UGR < 19 - DALI - Neutral LED - L 3588 **Attention! Code no longer in production**

Technical description
LED module set up for housing in initial or intermediate system profiles, ideal for particularly long light lines. High efficiency down emission for Working profiles (with a controlled luminance micro-prismatic screen). DALI dimmable electronic control gear integrated in the luminaire. Extruded aluminium heat sink; high emission yield flux enhancer. Neutral 4000K LED

Installation
Module insertion on profiles facilitated by a quick coupling system.

Colour Indeterminate (00) White (01)	Weight (Kg) 4.1
--	---------------------------

Wiring
Quick coupling terminal block connection to simplify connections between the subsequent modules. Complete with integrated dimmable digital DALI control gear.

Notes
Important: the triple length intermediate luminous module can be used for both initial profiles - L 3594 - for stand-alone applications, and intermediate profiles - L 3594 - for continuous line applications.

Complies with EN60598-1 and pertinent regulations



Technical data			
Im system:	5796.0	Colour temperature [K]:	4000
W system:	45.3	MacAdam Step:	3
Im source:	8050	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25C)
W source:	41	Voltage [Vin]:	230
Luminous efficiency (Im/W, real value):	127.95	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0.0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	72	Number of optical assemblies:	1
Beam angle [°]:	68° / 78°	Control:	DALI-2
CRI:	80		