



- Diffused light luminaire for use with incandescent and fluorescent lamps.
- Wall-mounted, ceiling-mounted and pole installation.
- Polycarbonate assembly structure; polycarbonate outer frame; moulded polycarbonate diffuser screen.
- Available with electronic control gear.
- Extruded aluminium pole.
- All screws are A2 stainless steel.



Ceiling mounted versions



Version with halo



White frame



Grey frame



ø 280



ø 326



ø 397



01
WHITE





15
GREY



W	code colour
Pole complete with luminaire	
A 60 (E27) - TC-TSE (E27)	
60W (A 60)	B850 15
20W (TC-TSE)	
TC-TEL (GX24q-3)	
Electronic	
26W	B852 15



W	dimens.	code colour
Luminaire		
A 60 (E27) - TC-TSE (E27)		
60W (A 60)	ø280 x h119	B828 01-15
20W (TC-TSE)		
TC-TEL (GX24q-3)		
Electronic		
26W	ø280 x h119	B830 01-15



W	dimens.	code colour
Luminaire with halo		
A 60 (E27) - TC-TSE (E27)		
60W (A 60)	ø280 x h119	B831 01-15
20W (TC-TSE)		
TC-TEL (GX24q-3)		
Electronic		
26W	ø280 x h119	B833 01-15



accessories

	code	colour
251x150  L=160 ø 16	0455	00 for B850-B852 B853-B855