


Last information update: June 2025

**Product configuration: SS76.15**

SS76.15: 47 surface Integral with side box - Wall/Ceiling-mounted - RGBW (W=4000K) - DMX - L = 340mm - Wall Grazing Wide Flood optic - Grey

**Product code**

SS76.15: 47 surface Integral with side box - Wall/Ceiling-mounted - RGBW (W=4000K) - DMX - L = 340mm - Wall Grazing Wide Flood optic - Grey

**Technical description**

Direct light luminaire, designed to use RGBW LED lamps, (W=4000K), 220÷240Vac DMX512-RDM dimmable with searching and addressing function. Ceiling, wall or surface-mounted. It consists of a body and installation brackets to be ordered separately. The body is made of extruded aluminium and includes die-cast aluminium end caps with 50/60 Shore A silicone seals. It is subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The following painting stage consists of a primer and a liquid acrylic paint, cured at 150°C, with a high level of weather and UV ray resistance. The top of the optical assembly is closed by a 3 mm thick transparent glass screen, fixed with silicone. Complete with multi-LED power plate in RGBW colour and a 220÷240Vac DMX512-RDM electronic driver (power supply included). The product is supplied with a nickel-plated brass PG13.5 single cable gland with an H07RN-F 5x1, 5mm<sup>2</sup> rubber outlet cable with an IP68 male connector. Fitted with a PMMA diffusing filter and optics with a plastic (methacrylate) lens for Wide Flood lighting. All external screws used are made of A2 stainless steel.

**Installation**

Installation accessories can be purchased separately, including arms (for heights &lt; 3m and heights &gt; 3m) and plates.

**Colour**

Grey (15)

**Mounting**

wall arm|wall surface

Complies with EN60598-1 and pertinent regulations



IK06



IP66



CE



pending

**Technical data**

|  |              |                                       |                               |
|--|--------------|---------------------------------------|-------------------------------|
| lm system:   | 651          | Life Time LED 1:                      | 86,000h - L80 - B10 (Ta 25°C) |
| W system:  | 16.5         | Life Time LED 2:                      | 81,000h - L80 - B10 (Ta 40°C) |
| lm source:   | 880          | Voltage [Vin]:                        | 230                           |
| W source:  | 11           | Lamp code:                            | LED                           |
| Luminous efficiency (lm/W, real value):            | 39.5         | Number of lamps for optical assembly: | 1                             |
| lm in emergency mode:                              | -            | ZVEI Code:                            | LED                           |
| Total light flux at or above an angle of 90° [Lm]: | 0            | Number of optical assemblies:         | 1                             |
| Light Output Ratio (L.O.R.) [%]:                   | 74           | Intervallo temperatura ambiente:      | from -30°C to 50°C.           |
| Colour temperature [K]:                            | RGBW - 4000K | Control:                              | DMX-RDM                       |

**Polar**