


Last information update: May 2024

Product configuration: BE56+L061

BE56: Ceiling-mounted recessed luminaire with IP66 protection rating, large body, 70W HIT G12 adjustable Spot

**Product code**BE56: Ceiling-mounted recessed luminaire with IP66 protection rating, large body, 70W HIT G12 adjustable Spot **Attention! Code no longer in production****Technical description**

Downlighter with HIT metal halide lamps with adjustable Spot optic. Consists of a round optical assembly, frame, lateral component holder box and an outer casing to be ordered separately where necessary. The optical assembly and frame are made of aluminium alloy, coated with liquid acrylic paint with a high level of weather and UV ray resistance. The tempered sodium - calcium sealing glass is transparent, with customised serigraphy on the edge, 5mm thick, joined to the frame with silicone. Reflectors made of 99.96% super-pure aluminium, fixed to the assembly by quick-coupling springs. Adjustable optic: $\pm 20^\circ$ about the vertical axis and 180° relative to the horizontal plane. Adjustable versions have a system for aiming the optic using a tool even when the lamp is on (without the risk of burns). Complete with a black-painted aluminium multi-groove ring. The lateral component holder box and top end cap are made of black-painted aluminium alloy, complete with a silicone internal seal to guarantee watertightness. The optical assembly and lateral box are connected by a stainless steel threaded connector with a cable gland rubber gasket for a watertight seal. Set up for pass-through wiring using two M24x1.5 nickel-plated brass cable glands, suitable for cables with diameter 7 - 16mm. Ceiling-mounting system consists of special A2 stainless steel screws complete with black aluminium alloy and plastic coupling supports. There is a single tool (No. 3 Allen key) for opening the frame, the lateral box cap and for the fixing system. The outer casing for concrete ceilings is made of black-painted ready-galvanised sheet aluminium complete with an end cap and threaded bar.

Installation

Recessed in false ceilings 5 - 60mm thick. Hole for preparation of false ceiling $\varnothing=212\text{mm}$. Installed on concrete ceilings using an outer casing, to be ordered separately.

Colour

Grey (15)

Mounting

ceiling surface

Wiring

Luminaire equipped with electronic ballast 220/240V 50/60Hz

Notes

Plastic adapter disk available for flush-mounting the frame on ceilings made of concrete exposed to view (can only be used with the product with aluminium frame, without the stainless cover). Products set up for installation of a stainless steel safety kit L=2000mm.

Complies with EN60598-1 and pertinent regulations

**Technical data**

Im system:	4231	CRI:	92
W system:	78	Colour temperature [K]:	4200
Im source:	6600	Voltage [Vin]:	230
W source:	70	Lamp code:	L061
Luminous efficiency (Im/W, real value):	54.2	Socket:	G12
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	HIT-CE
Light Output Ratio (L.O.R.) [%]:	64	Number of optical assemblies:	1
Beam angle $[\alpha]$:	10°	Intervallo temperatura ambiente:	from -20°C to $+35^\circ\text{C}$.

Polar

Imax=71973 cd		Lux			
		h	d	Em	Emax
	90°	2	0.3	14167	17993
	180°	4	0.7	3542	4498
	90°	6	1	1574	1999
	0°	8	1.4	885	1125
$\alpha = 10^\circ$					

R	77	75	73	71	55	53	33	00	DRR
K0.8	56	52	50	48	52	50	49	47	73
1.0	59	56	53	52	55	53	53	50	78
1.5	62	60	58	57	59	58	57	55	86
2.0	65	63	61	60	62	61	60	58	91
2.5	66	65	63	63	64	63	62	60	94
3.0	67	66	65	64	65	64	63	61	96
4.0	68	67	66	66	66	65	64	63	98
5.0	68	67	67	67	66	66	65	63	99

QC

	A	G	1.15	2000	1000	500	<=300		
	B		1.50		2000	1000	750	500	<=300
	C		1.85			2000		1000	500

85°
75°
65°
55°
45°

10² 2 3 4 5 6 8 10³ 2 3 4 5 6 8 10⁴

C0-180 C90-270

cd/m²