

## Palco Low Voltage


Design Artec  
Studio

iGuzzini

Last information update: March 2025

### Product configuration: Q636.01+MZ45.04

Q636.01: Palco LV spotlight Ø 51 - spot beam - 15.9W 1121.7lm - 3000K - CRI 90 - White  
MZ45.04: Honeycomb louvre - Black



### Product code

Q636.01: Palco LV spotlight Ø 51 - spot beam - 15.9W 1121.7lm - 3000K - CRI 90 - White

### Technical description

Miniaturised adjustable spotlight with adapter for installation on 48V low voltage track. Made of die-cast aluminium with passive dissipation system. The adapter made of a thermoplastic material includes the DC/DC driver circuit with a DALI dimmable function. Integrated «power line» technology allows each spotlight mounted on the track to be regulated separately. The swivel joints allow the spotlight to be rotated by 360° and tilted by 90°. The set back position of the optic unit guarantees a high level of visual comfort. Thermoplastic high definition lens with extra filter for variable optic. A rapid tool-free system for connecting the adapter electrically and mechanically to the track.

### Installation

Mechanical fastening with adapter on track.

### Colour

White (01)

### Weight (Kg)

0.28

### Mounting

Low voltage track

### Wiring

Integrated DC/DC LED driver in adapter - direct connection on 48V track. Track power supply unit to be ordered separately.

### Notes

Technical and anti-glare accessories available.

Complies with EN60598-1 and pertinent regulations



IP20



### Accessory code

MZ45.04: Honeycomb louvre - Black

### Technical description

Honeycomb louvre - reduces direct glare significantly.

### Installation

in contact with the accessory holder after the spacer ring has been removed.

### Colour

Black (04)

### Weight (Kg)

0.01

Complies with EN60598-1 and pertinent regulations



### Technical data

Im system:	715	Life Time LED 1:	> 50,000h - L90 - B10 (Ta 25°C)
W system:	15.9	Lamp code:	LED
Im source:	1460	Number of lamps for optical assembly:	1
W source:	15	ZVEI Code:	LED
Luminous efficiency (Im/W, real value):	45	Number of optical assemblies:	1
Im in emergency mode:	-	LED current [mA]:	400
Total light flux at or above an angle of 90° [Lm]:	0	Power factor:	See installation instructions
Light Output Ratio (L.O.R.) [%]:	49	Minimum dimming %:	5
Beam angle [°]:	14° / 13°	Overvoltage protection:	2kV Common mode & 1kV Differential mode
CRI (minimum):	90	Dimming mode:	CCR
Colour temperature [K]:	3000	Control:	DALI
MacAdam Step:	2		

Polar

