

QL75: Ø597mm - Tunable White - Opal - DALI



QL75: Ø597mm - Tunable White - Opal - DALI

Round luminaire for ceiling-mounted installation with option of recessed or pendant installation via an accessory to be ordered separately. Up/down emission designed to use Tunable White 2700K+6500K LED lamp . The optical assembly consists of an extruded painted aluminium frame, a satin finish methacrylate diffuser screen for general light emission and a sheet metal rear closing base. The DALI DT8 driver is housed in the upper part of the product.

Ceiling-mounted. Recessed or pendant-mounted using an accessory to be ordered separately.

Colour	Weight (Kg)
White (01) Black (04)	6.5

wall surface|ceiling surface

Product complete with electronic components. The electrical cables used are made of a "halogen free" material. (This means that the cables do not contain any halogen materials that in the event of a fire do not emit toxic or corrosive gases and only a small quantity of opaque fumes).

Complies with EN60598-1 and pertinent regulations



Im system:	3395	CRI (minimum):	90
W system:	29.9	Colour temperature [K]:	Tunable white 2700 - 6500
Im source:	4650	Life Time LED 1:	50,000h - L90 - B10 (Ta 25°C)
W source:	25	Lamp code:	LED
Luminous efficiency (lm/W, real value):	113.5	Number of lamps for optical assembly:	1
Im in emergency mode:	-	ZVEI Code:	LED
Total light flux at or above an angle of 90° [Lm]:	99	Number of optical assemblies:	1
Light Output Ratio (L.O.R.) [%]:	73	Control:	DALI-2

Imax=1154 cd

C80-260

CIE

nL 0.73

47-79-96-97-73

UGR 21.3-20.9

DIN

A.43

UTE

0.71E+0.02T

F"1=470

F"1+F"2=786

F"1+F"2+F"3=956