

Full Square

design Mario Cucinella





Features






- Diffused light luminaire for use with fluorescent lamps.
- Ceiling and wall-mounted installation also available in recessed version.
- Composed of component-holder compartment, front frame and protection screen.
- Polycarbonate compartment complete with: component holderplate with protection cover, control gear with fast-coupling terminals and PG11 cable clamp; diecast aluminium external frame; polycarbonate diffuser.
- Available with electronic control gear and emergency with inverter.
- Luminaire ready for pass-through wiring.
- All screws are A2 stainless steel.





	light source W		code colour
	TC-TEL (GX24q-3)	Electronic	
		26/32 W	B572 01-15
		Electronic	
		Always-on for emergency light	
		26 W	*B691 01-15
		* Wall-mounting only	



	light source W		code colour
	TC-TEL (GX24q-3/4)	Electronic	
		26/32 W	B573 01-15
		Electronic	
		Always-on for emergency light	
		26 W	*B691 01-15
		* Wall-mounting only	



installation systems

	code colour		code colour
	0045 00		BZH6 04
	The polystyrene is placed in the container either to create a housing for the fixture when set in concrete or to provide a finish for the housing for the wall-mounted unit.		for B573

Full



design Mario Cucinella




Features



- Luminaire for diffused light emission for use with incandescent (Full) and fluorescent (Screen/Full) lamps.
- Ceiling and wall-mounted installation also available in recessed version.
- Equipped with component compartment, frame, and diffusing screen.
- Polycarbonate compartment complete with component-holder plate with protection cover,
- control gear with fast-coupling terminals and PG11 cable clamp; die-cast aluminium external frame; diffuser made of internally painted textured glass.
- Available with electronic control gear and emergency with inverter.
- Luminaire ready for pass-through wiring.
- All screws are A2 stainless steel.




light source	W	ø	code colour
Wall/ceiling-mounted luminaire			
HALO ES (E27)	60 W max	275	7078 01-15
	75 W max	355	7040 01-15
TC-TEL (GX24q-3/4)	Electronic		
	26 W	275	B546 01-15
	26/32/42 W	355	B548 01-15
	2x26 W	355	B549 01-15
	Electronic Always-on for emergency light		
	26 W	355	B689 01-15
Wall/ceiling-mounted luminaire with halo			
HALO ES (E27)	60 W max	275	7082 01-15
	75 W max	355	7045 01-15
TC-TEL (GX24q-3/4)	Electronic		
	26 W	275	B547 01-15
	26/32/42 W	355	B550 01-15
	2x26 W	355	B551 01-15




light source	W	ø	code colour
Wall/ceiling-recessed luminaire			
TC-TEL (GX24q-3/4)	Electronic		
	26/32/42 W	355	B554 01-15

* Wall-mounting only

installation systems

	code	colour
 Body moulding cover The polystyrene is placed in the container either to create a housing for the fixture when set in concrete or to provide a finish for the housing for the wall-mounted unit.	0043	00 for B554

	code	colour
 Casing	BZH5	04 for B554