



Last information update: February 2025



**Product code**

2380: 5-cell recessed luminaire - LED - Warm White - Medium Oval - transversal optic

**Technical description**

Rectangular miniaturised recessed luminaire with 5 optical elements fitted with LED lamps - fixed Medium Oval optics - narrow opening asymmetrical emission with a transversal effect. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised thermoplastic high definition optics, integrated in a rear position in the black anti-glare screen. Supplied with DALI dimmable control gear unit connected to the luminaire.

**Installation**

recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 37 x 141

**Colour**

White (01) | Black / Black (43) | Black / White (47) | Grey / Black (74)\*

**Weight (Kg)**

0.3

\* Colours on request


**Mounting**

wall recessed|ceiling recessed

**Wiring**

on control gear box; screw connections with terminal block included

Complies with EN60598-1 and pertinent regulations



**Technical data**

lm system:	847 (*)	CRI:	90
W system:	10 (*)	Colour temperature [K]:	3500
lm source:	1193 (*)	Number of lamps for optical assembly:	1
W source:	10 (*)	ZVEI Code:	LED
Luminous efficiency (lm/W, real value):	84.0 (*)	Number of optical assemblies:	1
lm in emergency mode:	-	Control:	DALI-2