


Last information update: May 2024

**Product configuration: MP91**

MP91: Medium body spotlight - warm white - electronic ballast and dimmer - medium optic

**Product code**MP91: Medium body spotlight - warm white - electronic ballast and dimmer - medium optic **Attention! Code no longer in production****Technical description**

Pendant luminaire equipped with a multiphase adapter made of die-cast aluminium and thermoplastic material. The pendant system consists of steel cables L=2000 that provide a simple mechanical anchoring system. Having been rotated and tilted, the luminaire can be locked mechanically in position to ensure efficient light aiming (even during maintenance operations). Luminaire for high output LED lamp with monochrome emission in a warm white colour tone (3000K). Dimmable electronic ballast. Equipped with an accessory holding ring designed to contain a flat accessory. Another external component can also be applied, selected from directional flaps and an asymmetric screen. All external accessories rotate 360° about the spotlight longitudinal axis.

**Installation**

Mounted on an electrified track with a multiphase adapter.

**Colour**

White (01) | Grey / Black (74)

**Mounting**

ceiling pendant

**Wiring**

The dimmable electronic components are housed in the luminaire.

Complies with EN60598-1 and pertinent regulations



850°C

IP20

IP40

for optical assembly

**Technical data**

Im system:	2332	CRI (minimum):	80
W system:	25	Colour temperature [K]:	3000
Im source:	3000	MacAdam Step:	3
W source:	23	Life Time LED 1:	50,000h - L80 - B10 (Ta 25°C)
Luminous efficiency (Im/W, real value):	93.3	Lamp code:	LED
Im in emergency mode:	-	Number of lamps for optical assembly:	1
Total light flux at or above an angle of 90° [Lm]:	0	ZVEI Code:	LED
Light Output Ratio (L.O.R.) [%]:	78	Number of optical assemblies:	1
Beam angle [°]:	14°		

**Polar**