

Cerchio - Zoom

design Bruno Gecchelin



Cerchio



Zoom

Features



Cerchio

- Installation on low voltage track, Mini Limelight.
- Made of die-cast aluminium and thermoplastic material.
- 305° rotation around the vertical axis and inclination of 130° (35W) - 122° (50W) in relation to the horizontal plane.




Zoom


- Installation on low voltage track, Mini Limelight.
- Made of die-cast aluminium and thermoplastic material.
- 360° rotation around the vertical axis and inclination of 140° in relation to the horizontal plane.
- The fitting has a patented joint system that makes it highly adjustable and assures electrical conductivity.




Optics and lamps



S - Spot



M - Medium




F - Flood

QR-CBC 35	35 - 50W
QR-CBC 51	35 - 50W


Fitting on a curved rod

Mini Limelight, the low voltage track solution especially studied to illuminate paintings.






Cerchio




light source	W	code	colour
QR CBC 35 (GU4)	Straight rod L=70		
	35 W 12 V	6327	15
	Straight rod L=300		
	50 W 12 V	6328	15
QR CBC 51 (GU5,3)	Straight rod L=70		
	35 W 12 V	6329	15
	Straight rod L=300		
	50 W 12 V	6330	15



QR CBC 35 (GU4)	Curved rod		
	35 W 12 V	6334	15
QR CBC 51 (GU5,3)	Curved rod		
	50 W 12 V	6335	15

Zoom



light source	W	code	colour
QR CBC 51 (GU5,3)	Straight rod L=70		
	50 W 12 V	6314	01-15
	Straight rod L=300		
	50 W 12 V	6315	01-15
	Straight rod L=500		
	50 W 12 V	6316	01-15
	Straight rod L=800		
	50 W 12 V	6317	01-15

accessories



Coloured filters

code	colour	code	colour
---	---	8658	05-06-09 24 65



Directional flaps

6000	04	8740	04
for QR CBC35			
6001	04		
for QR CBC51			



Base with 50 W
electronic transformer,
for ceiling application

6091	01-15	6091	01-15
h46 - ø123		h46 - ø123	



Recessed base
Hole for installation 63 mm

6092	01-15	6092	01-15
h89 - ø71		h89 - ø71	