





Laser Blade XS Superrail module is a linear miniaturised luminaire with an invisible light source. Despite the ultra compact size of the product, the patented technology of the Opti Beam micro optic system guarantees an efficient luminous flux and a high level of visual comfort. The wall washer version insure a homogeneous emission on the wall without shadow zones near the ceiling. Perfect for retail and hospitality environments. To be installed on the Superrail 48V track system with a rapid tool-free connecting system. The adapter includes dimming capability allowing each light module to be adjusted separately.



Luminaire characteristics:	Power input: 5.9W to 21.9W (system wattage) Lumens: 294lm to 1535lm (for 3000K, 90CRI) Luminaire efficacy: Up to 79lm/W
Source:	White LED (LM-80) 2700K: 90CRI, 3500K: 90CRI, 3000K: 90CRI, 4000K: 90CRI.
Lumen maintenance:	80% of initial lumens at 50 000 hours (L80) (LM79)
Optics:	Low luminance Opti Beam technology with flood, general light pro and wall washer distribution. See page 5 for detailed offering.
Material:	Body: extruded aluminum Reflector and baffles: metalized thermoplastic Adapter: thermoplastic
Mounting:	Mechanical fastening on Superrail track.
Electrical:	Superrail 48V track with remote power supply (Class 2 wiring).
Dimming:	0-10V single channel for complete track control. DALI individual fixture addressing and control. Refer to iGuzzini Superrail track specification for dimming options.
Finish:	Black or white (RAL9010) painted finish.
Weight:	0.17lb (0.08kg) to 0.30lb (0.14kg)
Warranty:	5 year limited warranty.
Ratings:	IP20
Certification:	cULus listed for dry location



ORDERING INFO

ILBXS - SR - T - - - -
FIXTURE

MODEL

☐ **05** - Five

☐ **10** - Ten

VOLTAGE

☒ **SR** - Superrail

MOUNTING

☒ **T** - Track

OUTPUT

☐ **BO** - Base output ⁽²⁾

☐ **HO** - High output

LED

☐ **927** - 2700K, 90 CRI

☐ **930** - 3000K, 90 CRI

☐ **935** - 3500K, 90 CRI

☐ **940** - 4000K, 90 CRI

OPTIC

☐ **FL** - Flood 42°

☐ **GP** - General light pro ⁽¹⁾

☐ **WL** - Wall washer LGC ⁽¹⁾

FINISH (body finish / baffle finish)

☐ **01** - White / Black

☐ **02** - Black / Black

☐ **31** - White / White


⁽¹⁾ Available for high output (HO)

⁽²⁾ Available for continuous line application

DIMENSIONS


**LASER BLADE XS05
TRACK DOWNLIGHT**

OPTICS:
HIGH CONTRAST
GENERAL LIGHT PRO
WALL WASHER LGC



**LASER BLADE XS10
TRACK DOWNLIGHT**


OPTICS:
HIGH CONTRAST
GENERAL LIGHT PRO
WALL WASHER LGC



CONTINUOUS LINE APPLICATION



CONTINUOUS LINE EXAMPLE




*For remaining empty track, you can cut on site or use the cover strip IPB59. See accessories section in Superrail specification sheet for more details.

PHOTOMETRIC DATA

Visit iguzzini.com/us for complete photometric data.

TRACK MODEL

LBXS05




FL GP LGC


CCT (K)	CRI	OUTPUT	LOAD (W)	OPTIC	LUMENS (lm)	EFFICACY (lm / w)	MAX CANDELA (cd)	MODEL
3000K	90	BO	5.9 W	Flood 42°	431	73	886	ILBXS05-SR-T-BO-930-FL
		HO	11.6 W	Flood 42°	771	66	1 585	ILBXS05-SR-T-HO-930-FL
				General light pro	762	65	634	ILBXS05-SR-T-HO-930-GP
				wall washer LGC	294	25	290	ILBXS05-SR-T-HO-930-WL

*USE MULTIPLIER TABLE BELOW FOR OTHER CCT AND CRI OUTPUT DATA


HO flood 42° (3000K, 90 CRI)



HO general light pro (3000K, 90 CRI)



HO wall washer LGC (3000K, 90 CRI)



Center Beam fc	Beam Width ft
392	1.5
98.0	3.0
43.6	4.6
24.5	6.1
15.7	7.6
10.9	9.1

Center Beam fc	Beam Width ft
191	2.1
47.6	4.1
21.2	6.2
11.9	8.3
7.62	10.4
5.29	12.4


CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	0.94	1	1.06	1.12

PHOTOMETRIC DATA

Visit iguzzini.com/us for complete photometric data.

TRACK MODEL

LBXS10




FL GP LGC

CCT (K)	CRI	OUTPUT	LOAD (W)	OPTIC	LUMENS (lm)	EFFICACY (lm / w)	MAX CANDELA (cd)	MODEL
3000K	90	BO	10.9 W	Flood 42°	871	79	1 780	ILBXS10-SR-T-BO-930-FL
		HO	21.7 W	Flood 42°	1 535	70	3 153	ILBXS10-SR-T-HO-930-FL
				General light pro	1 276	58	1 533	ILBXS10-SR-T-HO-930-GP
			18.7 W	wall washer LGC	528	28	520	ILBXS10-SR-T-HO-930-WL


*USE MULTIPLIER TABLE BELOW FOR OTHER CCT AND CRI OUTPUT DATA

HO flood 42° (3000K, 90 CRI)




Center Beam fc	Beam Width ft
2ft	780
4ft	195
6ft	86.7
8ft	48.7
10ft	31.2
12ft	21.7

HO general light pro (3000K, 90 CRI)



Center Beam fc	Beam Width ft
2ft	383
4ft	95.8
6ft	42.6
8ft	24.0
10ft	15.3
12ft	10.6

HO wall washer LGC (3000K, 90 CRI)



CCT options	2700K	3000K	3500K	4000K
CRI options	90CRI	90CRI	90CRI	90CRI
Multiplier	0.94	1	1.06	1.12