

Design iGuzzini iGuzzini Bespoke

Product configuration: SG07

Product code

Technical description

Installation

Colour
Grey (RAL 7010) (U9)

Weight (Kg)
2.72

Mounting

pole-top

Complies with EN60598-1 and pertinent regulations



Technical data

| | | | |
|--|--------------------------------|---------------------------------------|---|
| Im system: | 2300 | Life Time LED 2: | 100,000h - L90 - B10 (Ta 40°C) |
| W system: | 15 | Voltage [Vin]: | 230 |
| Im source: | - | Lamp code: | LED |
| W source: | - | Number of lamps for optical assembly: | 1 |
| Luminous efficiency (Im/W, real value): | 153.3 | ZVEI Code: | LED |
| Im in emergency mode: | - | Number of optical assemblies: | 1 |
| Total light flux at or above an angle of 90° [Lm]: | 0 | Intervallo temperatura ambiente: | from -40°C to 50°C. |
| Light Output Ratio (L.O.R.) [%]: | 100 | Power factor: | See installation instructions |
| CRI (minimum): | 70 | Inrush current: | 24.88 A / 236 µs |
| Colour temperature [K]: | 3000 | Minimum dimming %: | 5 |
| MacAdam Step: | 5 | Overvoltage protection: | 10kV Common mode & 10kV Differential mode |
| Life Time LED 1: | 100,000h - L90 - B10 (Ta 25°C) | Control: | Middle of the night |

Polar

